

APPLICATION

SPRAY: Generally PVA Mold Release is applied by spraying. (TAP's PREVAL Sprayer is an economical applicator.) When applying with spray gun, use a small orifice and 60 to 90 psi air pressure and close the needle halfway. Spray at a distance of 12 to 18 inches, applying a mist coat first and following with a heavier coat. Best results obtained when spray density allows the liquid to flow together and form a continuous film.

BRUSH: You can also apply PVA by painting with a soft-bristle brush. Coat surface in one stroke, as a second coat will dissolve the first.

One gallon will cover approximately 400 square feet. Drying time is from 15 to 30 minutes under normal weather conditions. Wash equipment with water. PVA is only soluble in products containing water.

MSDS for TAP PVA Mold Release available at tapplastics.com

Allows Smooth Gloss Finish



Water Soluble Liquid Mold Release
For Polyester and Epoxy Resins

WARNING: FLAMMABLE LIQUID.
Read **CAUTIONS** On Right Panel.

Net 32 oz.

TAP Plastics
San Leandro CA 94577

CAUTIONS: FLAMMABLE LIQUID.

Avoid Open Flames, Hot Surfaces, or Any Ignition Source. Contains Ethyl Alcohol and Butyl Alcohol.

Inhalation: May cause headache, dizziness, incoordination, unconsciousness.

Skin: May cause irritation.

Eyes: Irritation to conjunctiva.

Ingestion: May cause nausea, vomiting, gastrointestinal bleeding, abdominal pain, and central nervous system depression depending on quantity ingested.

KEEP OUT OF REACH OF CHILDREN.

FIRST AID:

Inhalation • Expose victim to fresh air or oxygen. If breathing stops, begin artificial respiration and seek medical attention.

Skin • Wash with soap and water. If irritation persists, seek medical attention.

Eyes • Flush immediately with cold water for 15 min. Get medical attention.

Ingestion • Seek immediate medical attention.

Rev. 11811