

## 1 . Product and company identification

<b>Trade name</b>	: Amazing GOOP Automotive Epoxy Paste Hardener
<b>Supplier</b>	: Eclectic Products Inc. 1075 Arrowsmith Eugene, OR 97402 541-484-9621
<b>Material uses</b>	: Consumer products: Consumer product.
<b>Manufacturer</b>	: Eclectic Products Inc. 1075 Arrowsmith Eugene, OR 97402 541-484-9621
<b>Code</b>	: 1085351A
<b>Validation date</b>	: <b>5/14/2010.</b>
<b>Print date</b>	: 5/14/2010.
<b>Responsible name</b>	: <b>Regulatory Compliance</b>
<b><u>In case of emergency</u></b>	: CALL INFOTRAC 800-535-5053 001-352-323-3500

## 2 . Hazards identification

<b>Physical state</b>	: Liquid. [Paste.]
<b>Emergency overview</b>	: WARNING !  CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC RESPIRATORY AND SKIN REACTION. MAY BE HARMFUL IF ABSORBED THROUGH SKIN OR IF SWALLOWED.  Harmful in contact with skin and if swallowed. Severely irritating to the eyes, skin and respiratory system. May cause sensitization by inhalation and skin contact. Do not breathe vapor or mist. Do not ingest. Do not get in eyes or on skin or clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.
<b>Routes of entry</b>	: Dermal contact. Eye contact. Inhalation.
<b><u>Potential acute health effects</u></b>	
<b>Inhalation</b>	: Severely irritating to the respiratory system. May cause sensitization by inhalation. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.
<b>Ingestion</b>	: Harmful if swallowed.
<b>Skin</b>	: Harmful in contact with skin. Severely irritating to the skin. May cause sensitization by skin contact.
<b>Eyes</b>	: Severely irritating to eyes. Risk of serious damage to eyes.
<b><u>Potential chronic health effects</u></b>	
<b>Chronic effects</b>	: No known significant effects or critical hazards.
<b>Carcinogenicity</b>	: No known significant effects or critical hazards.
<b>Mutagenicity</b>	: No known significant effects or critical hazards.
<b>Teratogenicity</b>	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
<b>Fertility effects</b>	: No known significant effects or critical hazards.
<b>Target organs</b>	: Contains material which may cause damage to the following organs: gastrointestinal tract, upper respiratory tract, skin, eyes.
<b><u>Over-exposure signs/symptoms</u></b>	

## 2 . Hazards identification

- Inhalation** : Adverse symptoms may include the following:  
respiratory tract irritation  
coughing  
wheezing and breathing difficulties  
asthma
- Ingestion** : No specific data.
- Skin** : Adverse symptoms may include the following:  
irritation  
redness
- Eyes** : Adverse symptoms may include the following:  
pain or irritation  
watering  
redness
- Medical conditions aggravated by over-exposure** : Pre-existing respiratory, skin and digestive disorders may be aggravated by over-exposure to this product.

See toxicological information (section 11)

## 3 . Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Paratertiarybutylphenol	98-54-4	5-10
Diethylenetriamine	111-40-0	1-5
Benzyl Alcohol	100-51-6	1-5
Triethylenetetramine	112-24-3	1-5
Crystalline Silica	14808-60-7	<1

**There are no ingredients or additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## 4 . First aid measures

- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention. Chemical burns must be treated promptly by a physician.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Move exposed person to fresh air. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours. In the event of any complaints or symptoms, avoid further exposure.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

## 4 . First aid measures

- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing or wear gloves.
- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

## 5 . Fire-fighting measures

- Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst.
- Extinguishing media**
- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.
- Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
- Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides  
nitrogen oxides
- Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems or asthma, allergies or chronic or recurrent respiratory disease should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

## 7 . Handling and storage

**Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8 . Exposure controls/personal protection

### Product name

Diethylenetriamine

### Exposure limits

**ACGIH TLV (United States, 1/2009). Skin**

TWA: 4.2 mg/m<sup>3</sup> 8 hour(s).

TWA: 1 ppm 8 hour(s).

**NIOSH REL (United States, 6/2008). Skin**

TWA: 4 mg/m<sup>3</sup> 10 hour(s).

TWA: 1 ppm 10 hour(s).

**OSHA PEL 1989 (United States, 3/1989).**

TWA: 4 mg/m<sup>3</sup> 8 hour(s).

TWA: 1 ppm 8 hour(s).

Benzyl Alcohol

**AIHA WEEL (United States, 1/2009).**

TWA: 10 ppm 8 hour(s).

Triethylenetetramine

**AIHA WEEL (United States, 1/2009). Skin**

TWA: 1 ppm 8 hour(s).

Crystalline Silica

**ACGIH TLV (United States, 1/2009). Notes: Respirable fraction; see Appendix C, paragraph C.**

TWA: 0.025 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction

**NIOSH REL (United States, 6/2008). Notes: See Appendix A - NIOSH Potential Occupational Carcinogen**

TWA: 0.05 mg/m<sup>3</sup> 10 hour(s). Form: respirable dust

**OSHA PEL 1989 (United States, 3/1989). Notes: as quartz**

TWA: 0.1 mg/m<sup>3</sup>, (as quartz) 8 hour(s). Form: Respirable dust

**OSHA PEL Z3 (United States, 9/2005).**

TWA: 10 mg/m<sup>3</sup> 8 hour(s). Form: Respirable

TWA: 30 mg/m<sup>3</sup> 8 hour(s). Form: Total dust.

TWA: 250 mppcf 8 hour(s). Form: Respirable

### Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

### Engineering measures

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

### Hygiene measures

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

### Personal protection

#### Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

#### Hands

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

#### Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.

#### Skin

: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

## 8 . Exposure controls/personal protection

**Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

**Precautions to be taken in use:** : This product may contain materials classified as nuisance particulates, which may be present at hazardous levels only during sanding or abrading of the dried film. Wear a dust/mist respirator approved for dust when dusts are generated from sanding or abrading the dried film.

## 9 . Physical and chemical properties

**Physical state** : Liquid. [Paste.]  
**Flash point** : Open cup: >100°C (>212°F)  
**Color** : White.  
**Odor** : Ammoniacal.  
**Boiling/condensation point** : >100°C (>212°F)  
**Specific gravity** : 1.76  
**Vapor pressure** : <2.7 kPa (<20 mm Hg)  
**Estimated Vapor Density** : >1 [Air = 1]  
**VOC %** : 1.73434%  
**Evaporation rate** : >1 (Butyl acetate. = 1)  
**Solubility** : Very slightly soluble in the following materials: water.

## 10 . Stability and reactivity

**Stability** : The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur.  
**Conditions to avoid** : No specific data.  
**Materials to avoid** : No specific data.  
**Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.  
**Hazardous polymerization** : Will not occur.

## 11 . Toxicological information

### Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
Paratertiarybutylphenol	LD50 Dermal	Rabbit	2520 uL/kg	-
	LD50	Rat	225 mg/kg	-
	Intraperitoneal			
Diethylenetriamine	LD50 Oral	Rat	3250 uL/kg	-
	LD50 Dermal	Rabbit	1090 mg/kg	-
	LD50	Rat	74 mg/kg	-
	Intraperitoneal			
Benzyl Alcohol	LD50 Oral	Rat	1080 mg/kg	-
	LD50 Unreported	Rat	970 mg/kg	-
	LD50 Dermal	Rabbit	2000 mg/kg	-
	LD50 Intra-arterial	Rat	441 mg/kg	-
	LD50	Rat	400 mg/kg	-
	Intraperitoneal			
	LD50 Intravenous	Rat	53 mg/kg	-
	LD50 Oral	Rat	1660 mg/kg	-
	LD50 Oral	Rat	1230 mg/kg	-
	LD50 Oral	Rat	1.5 mL/kg	-
	LDLo	Rat	650 mg/kg	-
Intraperitoneal				
LDLo	Rat	1700 mg/kg	-	
Subcutaneous				
TDLo	Rat	514 mg/kg	-	

## 11 . Toxicological information

Triethylenetetramine	Intraperitoneal				
	LD50 Dermal	Rabbit	805 mg/kg	-	
Crystalline Silica	LD50 Oral	Rat	2500 mg/kg	-	
	LDLo	Rat	250 mg/kg	-	
	Intratracheal				
	LDLo	Rat	>200 mg/kg	-	
	Intratracheal				
	LDLo Intravenous	Rat	90 mg/kg	-	
	TDLo	Rat	100 mg/kg	-	
	Intratracheal				
	TDLo	Rat	50 mg/kg	-	
	Intratracheal				
	TDLo	Rat	30 mg/kg	-	
	Intratracheal				
	TDLo	Rat	25 mg/kg	-	
	Intratracheal				
	TDLo	Rat	15.69 mg/kg	-	
	Intratracheal				
	TDLo	Rat	10 mg/kg	-	
Intratracheal					
TDLo	Rat	10 mg/kg	-		
Intratracheal					
TDLo	Rat	5 mg/kg	-		
Intratracheal					
TDLo	Rat	1.5 mg/kg	-		
Intratracheal					
TDLo	Rat	1 mg/kg	-		
Intratracheal					
TDLo	Rat	1 mg/kg	-		
Intratracheal					
TDLo	Rat	1250 ug/kg	-		
Intratracheal					
TDLo	Rat	150 mg/kg	-		
Intratracheal					
TDLo	Rat	150 mg/kg	-		
Intratracheal					
TDLo Oral	Rat	120 g/kg	-		

### Carcinogenicity

#### Conclusion/Summary

Limestone and natural iron oxide used in making this product contain crystalline silica as an impurity. Repeated, prolonged exposure to respirable crystalline dusts may increase the risk of developing a disabling lung disease called silicosis. The International Agency for Research on Cancer (IARC) reports there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica from occupational sources. Based on studies of workers in industrial and occupational settings, The National Toxicology Program (NTP) Ninth Report on Carcinogens lists crystalline silica (respirable) as a substance known to be a carcinogen to humans.

### Classification

#### Product/ingredient name

Crystalline Silica

**ACGIH**

A2

**IARC**

1

**EPA**

-

**NIOSH**

+

**NTP**

Proven.

**OSHA**

-

#### IDLH

: Not available.

#### Synergistic products

: Not available.

## 12 . Ecological information

**Environmental effects** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

Product/ingredient name	Test	Result	Species	Exposure
Paratertiarybutylphenol	-	Acute EC50 3900 ug/L Fresh water	Daphnia -	48 hours
	-	Acute LC50 6.9 mg/L Fresh water	Daphnia magna	
	-	Acute LC50 5140 ug/L Fresh water	Fish - Cyprinus carpio	96 hours
Diethylenetriamine	-	Acute LC50 1014000 ug/L Fresh water	Fish - Pimephales promelas	96 hours
	-	Acute LC50 53500 ug/L Fresh water	Fish - Poecilia reticulata	96 hours
Benzyl Alcohol	-	Acute LC50 460000 ug/L Fresh water	Daphnia -	48 hours
	-	Acute LC50 15000 ug/L Marine water	Daphnia magna	
	-	Acute LC50 10000 ug/L Fresh water	Fish - Pimephales promelas	96 hours
Triethylenetetramine	-	Acute LC50 460000 ug/L Fresh water	Fish - Menidia beryllina	96 hours
	-	Acute LC50 15000 ug/L Marine water	Fish - Lepomis macrochirus	96 hours
	-	Acute LC50 33900 ug/L Fresh water	Fish - Daphnia magna	96 hours

**Conclusion/Summary** : Not available.

### Biodegradability

**Conclusion/Summary** : Not available.


## 13 . Disposal considerations

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.



Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
<b>DOT Classification</b>	Not available.	Consumer commodity	ORM-D	-		<b>Remarks</b> < 1 . 3 gal Consumer commodity ORM-D
<b>TDG Classification</b>	1760	CORROSIVE LIQUID, N.O.S. (Paratertiarybutylphenol, Triethylenetetramine)	8	III		-



## 14 . Transport information

<b>IMDG Class</b>	1760	CORROSIVE LIQUID, N.O.S. (Paratertiarybutylphenol, Triethylenetetramine)	8	III		<b>Emergency schedules (EmS)</b> F-A, S-B  <b>Remarks</b> Limited quantity
<b>IATA-DGR Class</b>	8000	Consumer commodity	9	-		-

PG\* : Packing group

## 15 . Regulatory information

**United States inventory (TSCA 8b):** All components are listed or exempted.  
SARA 311/312 - Acute, Chronic

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer.

#### Ingredient name

Crystalline Silica

#### Cancer

Yes.

#### Reproductive

No.

### Canada

#### **WHMIS (Canada)**

- : Class D-1B: Material causing immediate and serious toxic effects (Toxic).
- Class D-2A: Material causing other toxic effects (Very toxic).
- Class D-2B: Material causing other toxic effects (Toxic).
- Class E: Corrosive material

#### **Canadian lists**

- : **CEPA Toxic substances:** None of the components are listed.
- Canadian NPRI:** None of the components are listed.

#### **Canada inventory**

- : **Canada inventory:** All components are listed or exempted.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

### Mexico

#### **Classification**

:



### EU regulations

#### **Hazard symbol or symbols**

:



#### **Risk phrases**

- : R36/38- Irritating to eyes and skin.
- R43- May cause sensitization by skin contact.

#### **Safety phrases**

- : S2- Keep out of the reach of children.
- S24- Avoid contact with skin.
- S37- Wear suitable gloves.
- S46- If swallowed, seek medical advice immediately and show this container or label.

### International regulations



## 15 . Regulatory information

**International lists** : **Australia inventory (AICS)**: All components are listed or exempted.  
**China inventory (IECSC)**: At least one component is not listed.  
**Korea inventory (KECI)**: All components are listed or exempted.  
**Philippines inventory (PICCS)**: All components are listed or exempted.  
**Japan inventory (ENCS)**: Not determined.

**Europe inventory**: Not determined.

## 16 . Other information

**Hazardous Material Information System (U.S.A.)** :

Health	*	2
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (U.S.A.)** :



**Date of printing** : 5/14/2010.  
**Date of issue** : 5/14/2010.  
**Date of previous issue** : No previous validation.  
**Version** : 0.01

Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

## 1 . Product and company identification

<b>Trade name</b>	: Amazing GOOP Automotive Epoxy Paste Resin
<b>Supplier</b>	: Eclectic Products Inc. 1075 Arrowsmith Eugene, OR 97402 541-484-9621
<b>Material uses</b>	: Consumer products: Consumer product.
<b>Manufacturer</b>	: Eclectic Products Inc. 1075 Arrowsmith Eugene, OR 97402 541-484-9621
<b>Code</b>	: 1085350A
<b>Validation date</b>	: <b>5/18/2010.</b>
<b>Print date</b>	: 5/18/2010.
<b>Responsible name</b>	: <b>Regulatory Compliance</b>
<b><u>In case of emergency</u></b>	: CALL INFOTRAC 800-535-5053 001-352-323-3500

## 2 . Hazards identification

<b>Physical state</b>	: Liquid. [Paste.]
<b>Emergency overview</b>	: WARNING !  CAUSES EYE AND SKIN IRRITATION. MAY CAUSE ALLERGIC SKIN REACTION.  Irritating to eyes and skin. May cause sensitization by skin contact. Do not breathe vapor or mist. Do not get on skin or clothing. Avoid contact with eyes. Wash thoroughly after handling.
<b>Routes of entry</b>	: Dermal contact. Eye contact. Inhalation.

### Potential acute health effects

<b>Inhalation</b>	: No known significant effects or critical hazards.
<b>Ingestion</b>	: No known significant effects or critical hazards.
<b>Skin</b>	: Irritating to skin. May cause sensitization by skin contact.
<b>Eyes</b>	: Irritating to eyes.

### Potential chronic health effects

<b>Chronic effects</b>	: No known significant effects or critical hazards.
<b>Carcinogenicity</b>	: No known significant effects or critical hazards.
<b>Mutagenicity</b>	: No known significant effects or critical hazards.
<b>Teratogenicity</b>	: No known significant effects or critical hazards.
<b>Developmental effects</b>	: No known significant effects or critical hazards.
<b>Fertility effects</b>	: No known significant effects or critical hazards.

### Over-exposure signs/symptoms

<b>Inhalation</b>	: No specific data.
<b>Ingestion</b>	: No specific data.
<b>Skin</b>	: Adverse symptoms may include the following: irritation redness
<b>Eyes</b>	: Adverse symptoms may include the following: pain or irritation watering redness

## 2 . Hazards identification

**Medical conditions aggravated by over-exposure** : Pre-existing skin disorders may be aggravated by over-exposure to this product.

See toxicological information (section 11)

## 3 . Composition/information on ingredients

<u>Name</u>	<u>CAS number</u>	<u>%</u>
Bisphenol A/Epichlorohydrin Based Epoxy Resin	25085-99-8	30-60
Bisphenol F/Epichlorohydrin Epoxy Resin	28064-14-4	5-10
Crystalline Silica	14808-60-7	<1

**There are no ingredients or additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.**

## 4 . First aid measures

- Eye contact** : Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.
- Skin contact** : Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing or wear gloves. Continue to rinse for at least 10 minutes. Get medical attention. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Inhalation** : Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Get medical attention if adverse health effects persist or are severe. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Ingestion** : Wash out mouth with water. Remove dentures if any. Move exposed person to fresh air. Keep person warm and at rest. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention if adverse health effects persist or are severe. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Protection of first-aiders** : No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing or wear gloves.
- Notes to physician** : No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## 5 . Fire-fighting measures

**Flammability of the product** : In a fire or if heated, a pressure increase will occur and the container may burst.

### Extinguishing media

- Suitable** : Use an extinguishing agent suitable for the surrounding fire.
- Not suitable** : None known.

**Special exposure hazards** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

**Hazardous combustion products** : Decomposition products may include the following materials:  
carbon oxides

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## 6 . Accidental release measures

- Personal precautions** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).
- Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
- Large spill** : Stop leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.
- Small spill** : Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble or absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7 . Handling and storage

- Handling** : Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not ingest. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
- Storage** : Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8 . Exposure controls/personal protection

### Product name

Crystalline Silica

### Exposure limits

**ACGIH TLV (United States, 1/2009). Notes: Respirable fraction; see Appendix C, paragraph C.**

TWA: 0.025 mg/m<sup>3</sup> 8 hour(s). Form: Respirable fraction

**NIOSH REL (United States, 6/2008). Notes: See Appendix A - NIOSH Potential Occupational Carcinogen**

TWA: 0.05 mg/m<sup>3</sup> 10 hour(s). Form: respirable dust

**OSHA PEL 1989 (United States, 3/1989). Notes: as quartz**

TWA: 0.1 mg/m<sup>3</sup>, (as quartz) 8 hour(s). Form: Respirable dust

**OSHA PEL Z3 (United States, 9/2005).**

TWA: 10 mg/m<sup>3</sup> 8 hour(s). Form: Respirable

TWA: 30 mg/m<sup>3</sup> 8 hour(s). Form: Total dust.

TWA: 250 mppcf 8 hour(s). Form: Respirable

- Recommended monitoring procedures** : If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.
- Engineering measures** : No special ventilation requirements. Good general ventilation should be sufficient to control worker exposure to airborne contaminants. If this product contains ingredients with exposure limits, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure below any recommended or statutory limits.

## 8 . Exposure controls/personal protection

- Hygiene measures** : Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Personal protection**
- Respiratory** : Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
- Hands** : Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
- Eyes** : Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts.
- Skin** : Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Environmental exposure controls** : Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.
- Precautions to be taken in use:** : This product may contain materials classified as nuisance particulates, which may be present at hazardous levels only during sanding or abrading of the dried film. Wear a dust/mist respirator approved for dust when dusts are generated from sanding or abrading the dried film.

## 9 . Physical and chemical properties

- Physical state** : Liquid. [Paste.]
- Flash point** : Closed cup: >93.333°C (>200°F) [Setaflash.]
- Color** : Gray.
- Odor** : Not available.
- Boiling/condensation point** : >100°C (>212°F)
- Specific gravity** : 1.46
- Estimated Vapor Density** : >1 [Air = 1]
- VOC %** : 0.115255%
- Evaporation rate** : >1 (Butyl acetate. = 1)
- Solubility** : Insoluble in the following materials: water.

## 10 . Stability and reactivity

- Stability** : The product is stable. Under normal conditions of storage and use, hazardous polymerization will not occur.
- Conditions to avoid** : No specific data.
- Materials to avoid** : No specific data.
- Hazardous decomposition products** : Under normal conditions of storage and use, hazardous decomposition products should not be produced.
- Hazardous polymerization** : Will not occur.

# 11 . Toxicological information

## Acute toxicity

<b>Product/ingredient name</b>	<b>Result</b>	<b>Species</b>	<b>Dose</b>	<b>Exposure</b>
Bisphenol A/Epichlorohydrin Based Epoxy Resin	LD50 Dermal	Rabbit	20000 mg/kg	-
Crystalline Silica	LD50 Oral	Rat	>5000 mg/kg	-
	LDLo	Rat	250 mg/kg	-
	Intratracheal	Rat	>200 mg/kg	-
	LDLo			
	Intratracheal	Rat	90 mg/kg	-
	LDLo Intravenous			
	TDL0	Rat	100 mg/kg	-
	Intratracheal	Rat	50 mg/kg	-
	TDL0			
	Intratracheal	Rat	30 mg/kg	-
	TDL0			
	Intratracheal	Rat	25 mg/kg	-
	TDL0			
	Intratracheal	Rat	15.69 mg/kg	-
	TDL0			
	Intratracheal	Rat	10 mg/kg	-
	TDL0			
	Intratracheal	Rat	10 mg/kg	-
	TDL0			
	Intratracheal	Rat	5 mg/kg	-
TDL0				
Intratracheal	Rat	1.5 mg/kg	-	
TDL0				
Intratracheal	Rat	1 mg/kg	-	
TDL0				
Intratracheal	Rat	1 mg/kg	-	
TDL0				
Intratracheal	Rat	1250 ug/kg	-	
TDL0				
Intratracheal	Rat	150 mg/kg	-	
TDL0				
Intratracheal	Rat	150 mg/kg	-	
TDL0				
Intratracheal	Rat	120 g/kg	-	

## Carcinogenicity

### Conclusion/Summary

Limestone and natural iron oxide used in making this product contain crystalline silica as an impurity. Repeated, prolonged exposure to respirable crystalline dusts may increase the risk of developing a disabling lung disease called silicosis. The International Agency for Research on Cancer (IARC) reports there is sufficient evidence in humans for the carcinogenicity of inhaled crystalline silica from occupational sources. Based on studies of workers in industrial and occupational settings, The National Toxicology Program (NTP) Ninth Report on Carcinogens lists crystalline silica (respirable) as a substance known to be a carcinogen to humans.

## Classification

<b>Product/ingredient name</b>	<b>ACGIH</b>	<b>IARC</b>	<b>EPA</b>	<b>NIOSH</b>	<b>NTP</b>	<b>OSHA</b>
Crystalline Silica	A2	1	-	+	Proven.	-

**IDLH** : Not available.

**Synergistic products** : Not available.

## 12 . Ecological information

**Environmental effects** : No known significant effects or critical hazards.

### Aquatic ecotoxicity

**Conclusion/Summary** : Not available.

### Biodegradability

**Conclusion/Summary** : Not available.

## 13 . Disposal considerations

**Waste disposal** : The generation of waste should be avoided or minimized wherever possible. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14 . Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated.	-	-	-		-
TDG Classification	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		-

PG\* : Packing group

## 15 . Regulatory information

**United States inventory (TSCA 8b):** All components are listed or exempted.  
SARA 311/312 - Acute, Chronic

### California Prop. 65

**WARNING:** This product contains a chemical known to the State of California to cause cancer.

#### Ingredient name

Crystalline Silica

#### Cancer

Yes.

#### Reproductive

No.

### Canada

#### WHMIS (Canada)

: Class D-2A: Material causing other toxic effects (Very toxic).  
Class D-2B: Material causing other toxic effects (Toxic).

#### Canadian lists

: **CEPA Toxic substances:** None of the components are listed.  
**Canadian NPRI:** None of the components are listed.

#### Canada inventory

: **Canada inventory:** Not determined.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

### Mexico

#### Classification

:



## 15 . Regulatory information



### EU regulations

**Risk phrases** : This product is not classified according to EU legislation.

### International regulations

**International lists** : **Australia inventory (AICS):** Not determined.  
**China inventory (IECSC):** Not determined.  
**Korea inventory (KECI):** Not determined.  
**Philippines inventory (PICCS):** Not determined.  
**Japan inventory (ENCS):** Not determined.  
**Europe inventory:** Not determined.

## 16 . Other information

**Hazardous Material Information System (U.S.A.)** :

Health	*	2
Flammability		1
Physical hazards		0

Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

**National Fire Protection Association (U.S.A.)** :



**Date of printing** : 5/18/2010.  
**Date of issue** : 5/18/2010.  
**Date of previous issue** : No previous validation.  
**Version** : 1

☑ Indicates information that has changed from previously issued version.

### Notice to reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.