



Material Safety Data Sheet

Copyright, 2006, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: 3M(TM) Marine Fiberglass Cleaner and Wax, P.N. 09009, 09010, 09010E, 09011
MANUFACTURER: 3M
DIVISION: Automotive Aftermarket

ADDRESS: 3M Center
 St. Paul, MN 55144-1000

EMERGENCY PHONE: 1-800-364-3577 or (651) 737-6501 (24 hours)

Issue Date: 10/02/2006
Supersedes Date: 06/27/2006

Document Group: 06-3260-4

Product Use:

Intended Use: Marine applications. Composition verified with Process Standard 11/15/01 bmh.
Specific Use: Marine cleaner/wax

SECTION 2: INGREDIENTS

| <u>Ingredient</u> | <u>C.A.S. No.</u> | <u>% by Wt</u> |
|--|-------------------|----------------|
| WATER | 7732-18-5 | 30 - 60 |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | 64742-47-8 | 10 - 25 |
| TRIPOLI (CRYSTALLINE SILICA) | 1317-95-9 | 10 - 20 |
| ALUMINUM SILICATE | 66402-68-4 | 3 - 7 |
| CARNAUBA WAX | 8015-86-9 | 1 - 5 |
| POLY(DIMETHYLSILOXANE) | 63148-62-9 | 1 - 5 |
| MONTAN WAX | 8002-53-7 | < 5 |
| SOLVENT-REFINED HEAVY PARAFFINIC PETROLEUM DISTILLATES | 64741-88-4 | < 1.5 |
| CHLOROTHALONIL | 1897-45-6 | < 0.1 |
| FORMALDEHYDE | 50-00-0 | < 0.02 |

SECTION 3: HAZARDS IDENTIFICATION

3.1 EMERGENCY OVERVIEW

Specific Physical Form: Paste

Odor, Color, Grade: mild solvent odor, tan to beige color.

General Physical Form: Liquid

Immediate health, physical, and environmental hazards: Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back. Contains a chemical or chemicals which can cause cancer. May cause target organ effects.

3.2 POTENTIAL HEALTH EFFECTS

Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

Prolonged or repeated exposure may cause:

Silicosis: Signs/symptoms may include breathlessness, weakness, chest pain, persistent cough, increased amounts of sputum, and heart disease.

May be absorbed following inhalation and cause target organ effects.

Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

| <u>Ingredient</u> | <u>C.A.S. No.</u> | <u>Class Description</u> | <u>Regulation</u> |
|---|-------------------|------------------------------|---|
| CHLOROTHALONIL | 1897-45-6 | Group 2B | International Agency for Research on Cancer |
| FORMALDEHYDE | 50-00-0 | Group 1 | International Agency for Research on Cancer |
| FORMALDEHYDE | 50-00-0 | Anticipated human carcinogen | National Toxicology Program Carcinogens |
| FORMALDEHYDE | 50-00-0 | Cancer hazard | OSHA Carcinogens |
| SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE) | NONE | Group 1 | International Agency for Research on Cancer |
| SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE) | NONE | Known human carcinogen | National Toxicology Program Carcinogens |

SECTION 4: FIRST AID MEASURES

4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

Eye Contact: Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

Skin Contact: Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

Inhalation: Remove person to fresh air. If signs/symptoms develop, get medical attention.

If Swallowed: Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

SECTION 5: FIRE FIGHTING MEASURES

5.1 FLAMMABLE PROPERTIES

| | |
|--|--|
| Autoignition temperature | <i>No Data Available</i> |
| Flash Point | 150 - 170 °F [<i>Test Method:</i> Closed Cup] |
| Flammable Limits - LEL | <i>No Data Available</i> |
| Flammable Limits - UEL | <i>No Data Available</i> |
| OSHA Flammability Classification: | Class IIIB Combustible Liquid |

5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

5.3 PROTECTION OF FIRE FIGHTERS

Special Fire Fighting Procedures: Water may not effectively extinguish fire; however, it should be used to keep fire-exposed containers and surfaces cool and prevent explosive rupture. Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

Unusual Fire and Explosion Hazards: Combustible liquid and vapor. Closed containers exposed to heat from fire may build pressure and explode. Vapors may travel long distances along the ground or floor to an ignition source and flash back.

Note: See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Accidental Release Measures: Observe precautions from other sections. Call 3M- HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Collect as much of the spilled material as possible using non-sparking tools. Clean up residue with detergent and water. Place in a closed container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.

SECTION 7: HANDLING AND STORAGE

7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Keep away from heat, sparks, open flame, pilot lights and other sources of ignition. Avoid breathing of vapors, mists or spray. Avoid eye contact with vapors, mists, or spray. Avoid contact with oxidizing agents.

7.2 STORAGE

Store away from acids. Store away from heat. Store out of direct sunlight. Keep container in well-ventilated area. Store away from oxidizing agents.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers.

8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

8.2.1 Eye/Face Protection

Avoid eye contact with vapors, mists, or spray.

The following eye protection(s) are recommended: Safety Glasses with side shields, Indirect Vented Goggles.

8.2.2 Skin Protection

Avoid skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Nitrile Rubber.

8.2.3 Respiratory Protection

Avoid breathing of vapors, mists or spray.

Select one of the following NIOSH approved respirators based on airborne concentration of contaminants and in accordance with OSHA regulations: Half mask R95 particulate respirator, Half mask or full facepiece air-purifying respirator with N100 particulate filters, Half facepiece or fullface air-purifying respirator with P100 particulate filters, Half facepiece or fullface air-purifying respirator with P95 particulate filters, Half facepiece or fullface air-purifying respirator with N95 particulate filters. Consult the current 3M Respiratory Selection Guide for additional information or call 1-800-243-4630 for 3M technical assistance. Continuous spurring of dry buff pads may produce dust conditions in excess of the OSHA Permissible Exposure Limit (PEL) or the Threshold Limit Value (TLV) for crystalline silica. When cleaning or spurring a dry buff pad used with this product, use appropriate local exhaust to control dust, or use appropriate respiratory protection to avoid inhalation of dusts.

8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

8.3 EXPOSURE GUIDELINES

| <u>Ingredient</u> | <u>Authority</u> | <u>Type</u> | <u>Limit</u> | <u>Additional Information</u> |
|-------------------|------------------|-------------|--------------|-------------------------------|
| FORMALDEHYDE | ACGIH | CEIL | 0.3 ppm | Sensitizer; Table A2 |

| | | | | |
|---|-------|--------------------|-------------|-------------------|
| FORMALDEHYDE | OSHA | TWA | 0.5 ppm | Standard Appendix |
| HYDROTREATED LIGHT PETROLEUM DISTILLATES | CMRG | TWA | 300 ppm | |
| OIL MIST, MINERAL | ACGIH | TWA, as mist | 5 mg/m3 | |
| OIL MIST, MINERAL | ACGIH | STEL, as mist | 10 mg/m3 | |
| OIL MIST, MINERAL | OSHA | TWA, as mist | 5 mg/m3 | Table Z-1 |
| SOLVENT-REFINED HEAVY PARAFFINIC PETROLEUM DISTILLATES | CMRG | TWA | 5 mg/m3 | |
| STEARATES | ACGIH | TWA, as total dust | 10 mg/m3 | Table A4 |
| TRIPOLI (CRYSTALLINE SILICA) | ACGIH | TWA, respirable | 0.025 mg/m3 | Table A2 |
| TRIPOLI (CRYSTALLINE SILICA) | OSHA | TWA, respirable | 0.1 mg/m3 | Table Z-1A |
| VEGETABLE OIL MISTS | OSHA | TWA, as mist | 10 mg/m3 | Table Z-1A |
| VEGETABLE OIL MISTS (EXCEPT CASTOR, CASHEW, OR SIMILAR IRRITANT OILS) | ACGIH | TWA, as mist | 10 mg/m3 | |

SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists
 CMRG: Chemical Manufacturer Recommended Guideline
 OSHA: Occupational Safety and Health Administration
 AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|---|
| Specific Physical Form: | Paste |
| Odor, Color, Grade: | mild solvent odor, tan to beige color. |
| General Physical Form: | Liquid |
| Autoignition temperature | <i>No Data Available</i> |
| Flash Point | 150 - 170 °F [<i>Test Method:</i> Closed Cup] |
| Flammable Limits - LEL | <i>No Data Available</i> |
| Flammable Limits - UEL | <i>No Data Available</i> |
| Boiling point | 170 - 212 °F |
| Density | 8.9 - 9.4 lb/gal [<i>Details:</i> @ 77 +/- 3 degrees F] |
| Vapor Density | >=1.00 [<i>Ref Std:</i> AIR=1] |
| Vapor Pressure | <i>No Data Available</i> |
| Specific Gravity | 1.07 [<i>Ref Std:</i> WATER=1] |
| pH | 7.8 - 8.4 |
| Melting point | <i>No Data Available</i> |
| Solubility in Water | Moderate |
| Evaporation rate | >=1 [<i>Ref Std:</i> WATER=1] |
| Volatile Organic Compounds | 1.86 lb/gal [<i>Test Method:</i> calculated SCAQMD rule 443.1] |
| Percent volatile | 64.5 % |
| VOC Less H2O & Exempt Solvents | 419 g/l [<i>Test Method:</i> calculated SCAQMD rule 443.1] |
| Viscosity | 15000 - 25000 centipoise |

SECTION 10: STABILITY AND REACTIVITY

Stability: Stable.

Materials and Conditions to Avoid: Strong oxidizing agents

Hazardous Polymerization: Hazardous polymerization will not occur.

Hazardous Decomposition or By-Products

| <u>Substance</u> | <u>Condition</u> |
|-------------------------------|------------------|
| Carbon monoxide | Not Specified |
| Carbon dioxide | Not Specified |
| Toxic Vapor, Gas, Particulate | Not Specified |

SECTION 11: TOXICOLOGICAL INFORMATION

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION

Not determined.

CHEMICAL FATE INFORMATION

Not determined.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Method: Incinerate in an industrial or commercial facility. As a disposal alternative, dispose of waste product in a facility permitted to accept chemical waste.

EPA Hazardous Waste Number (RCRA): Not regulated

Since regulations vary, consult applicable regulations or authorities before disposal.

SECTION 14: TRANSPORT INFORMATION

ID Number(s):

60-9800-1769-7, 60-9800-2022-0, 60-9800-2023-8, 60-9800-2024-6, 60-9800-2589-8, 60-9800-2590-6, 60-9800-2591-4, 60-9800-3244-9, 60-9801-0695-3

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

SECTION 15: REGULATORY INFORMATION

US FEDERAL REGULATIONS

Contact 3M for more information.

311/312 Hazard Categories:

Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - Yes

STATE REGULATIONS

Contact 3M for more information.

CALIFORNIA PROPOSITION 65

| <u>Ingredient</u> | <u>C.A.S. No.</u> | <u>Classification</u> |
|---|-------------------|-----------------------|
| CHLOROTHALONIL | 1897-45-6 | **Carcinogen |
| FORMALDEHYDE | 50-00-0 | **Carcinogen |
| SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE) | NONE | **Carcinogen |

** WARNING: contains a chemical which can cause cancer.

CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact 3M for more information.

INTERNATIONAL REGULATIONS

Contact 3M for more information.

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

SECTION 16: OTHER INFORMATION

NFPA Hazard Classification

Health: 2 Flammability: 1 Reactivity: 0 Special Hazards: None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the

inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

Revision Changes:

Section 8: Exposure guidelines ingredient information was modified.

Section 16: Reason for reissue comment was deleted.

Section 16: Reason for reissue heading was deleted.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

3M MSDSs are available at www.3M.com