



## Material Safety Data Sheet

Copyright, 2007, 3M Company. All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

### SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** 3M(TM) Marine Outdoor Vinyl Cleaner, Conditioner and Protector; PN 09023

**MANUFACTURER:** 3M

**DIVISION:** Marine & Specialty Vehicle

**ADDRESS:** 3M Center  
St. Paul, MN 55144-1000

**EMERGENCY PHONE:** 1-800-364-3577 or (651) 737-6501 (24 hours)

**Issue Date:** 10/29/2007

**Supersedes Date:** 10/29/2007

**Document Group:** 18-3201-3

#### Product Use:

Specific Use: Improve and maintain the appearance of vinyl surfaces.  
Intended Use: Marine

### SECTION 2: INGREDIENTS

<u>Ingredient</u>	<u>C.A.S. No.</u>	<u>% by Wt</u>
Water	7732-18-5	60 - 100
POLY(DIMETHYLSILOXANE)	63148-62-9	10 - 30
TRIETHANOLAMINE	102-71-6	1 - 5
1-METHOXY-2-PROPANOL	107-98-2	1 - 5
AMINOMODIFIED POLYDIMETHYLSILOXANE	189959-16-8	0.5 - 5
POLYOXYETHYLENE TRIDECYL ETHER	24938-91-8	0.5 - 1.5
1,3,5-TRIAZINE-1,3,5(2H,4H,6H)-TRIETHANOL	4719-04-4	0.1 - 1

### SECTION 3: HAZARDS IDENTIFICATION

#### 3.1 EMERGENCY OVERVIEW

**Specific Physical Form:** Gel

**Odor, Color, Grade:** Off-white viscous liquid with a fragrance

**General Physical Form:** Liquid

**Immediate health, physical, and environmental hazards:** effects. May cause allergic skin reaction. May cause target organ effects.

## 3.2 POTENTIAL HEALTH EFFECTS

### Eye Contact:

Moderate Eye Irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

### Skin Contact:

Moderate Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, and dryness.

Allergic Skin Reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching.

### Inhalation:

Respiratory Tract Irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain.

May be absorbed following inhalation and cause target organ effects.

### Ingestion:

Gastrointestinal Irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

May be absorbed following ingestion and cause target organ effects.

### Target Organ Effects:

Central Nervous System (CNS) Depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

## SECTION 4: FIRST AID MEASURES

### 4.1 FIRST AID PROCEDURES

The following first aid recommendations are based on an assumption that appropriate personal and industrial hygiene practices are followed.

**Eye Contact:** Flush eyes with large amounts of water. If signs/symptoms persist, get medical attention.

**Skin Contact:** Remove contaminated clothing and shoes. Immediately flush skin with large amounts of water. Get medical attention. Wash contaminated clothing and clean shoes before reuse.

**Inhalation:** Remove person to fresh air. If signs/symptoms develop, get medical attention.

**If Swallowed:** Do not induce vomiting unless instructed to do so by medical personnel. Give victim two glasses of water. Never give anything by mouth to an unconscious person. Get medical attention.

## SECTION 5: FIRE FIGHTING MEASURES

### 5.1 FLAMMABLE PROPERTIES

Autoignition temperature

*No Data Available*

Flash Point	Not Applicable
Flammable Limits - LEL	Not Applicable
Flammable Limits - UEL	Not Applicable
OSHA Flammability Classification:	Not Applicable

## 5.2 EXTINGUISHING MEDIA

Use fire extinguishers with class B extinguishing agents (e.g., dry chemical, carbon dioxide).

## 5.3 PROTECTION OF FIRE FIGHTERS

**Special Fire Fighting Procedures:** Wear full protective equipment (Bunker Gear) and a self-contained breathing apparatus (SCBA).

**Unusual Fire and Explosion Hazards:** No unusual fire or explosion hazards are anticipated.

**Note:** See STABILITY AND REACTIVITY (SECTION 10) for hazardous combustion and thermal decomposition information.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

**Accidental Release Measures:** Refer to other sections of this MSDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment. Call 3M-HELPS line (1-800-364-3577) for more information on handling and managing the spill. Evacuate unprotected and untrained personnel from hazard area. The spill should be cleaned up by qualified personnel. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Warning! A motor could be an ignition source and could cause flammable gases or vapors in the spill area to burn or explode. Contain spill. For larger spills, cover drains and build dikes to prevent entry into sewer systems or bodies of water. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a toxic, corrosivity or flammability hazard. Collect as much of the spilled material as possible. Clean up residue with detergent and water. Place in a metal container approved for transportation by appropriate authorities. Dispose of collected material as soon as possible.

**In the event of a release of this material, the user should determine if the release qualifies as reportable according to local, state, and federal regulations.**

## SECTION 7: HANDLING AND STORAGE

### 7.1 HANDLING

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water. Avoid breathing of vapors, mists or spray. Avoid prolonged or repeated skin contact. Keep out of the reach of children. Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below Occupational Exposure Limits. If ventilation is not adequate, use respiratory protection equipment. Avoid eye contact with vapors, mists, or spray. Do not ingest.

### 7.2 STORAGE

Keep container in well-ventilated area.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 ENGINEERING CONTROLS

Use with appropriate local exhaust ventilation. Provide appropriate local exhaust ventilation on open containers.

## 8.2 PERSONAL PROTECTIVE EQUIPMENT (PPE)

### 8.2.1 Eye/Face Protection

Avoid eye contact.

The following eye protection(s) are recommended: Safety Glasses with side shields.

### 8.2.2 Skin Protection

Not applicable. Avoid prolonged or repeated skin contact.

Select and use gloves and/or protective clothing to prevent skin contact based on the results of an exposure assessment. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible materials.

Gloves made from the following material(s) are recommended: Nitrile Rubber, Polyvinyl Chloride.

### 8.2.3 Respiratory Protection

Under normal use conditions, airborne exposures are not expected to be significant enough to require respiratory protection.

During application:

Avoid breathing of vapors, mists or spray.

### 8.2.4 Prevention of Swallowing

Do not eat, drink or smoke when using this product. Wash exposed areas thoroughly with soap and water.

## 8.3 EXPOSURE GUIDELINES

<u>Ingredient</u>	<u>Authority</u>	<u>Type</u>	<u>Limit</u>	<u>Additional Information</u>
1-METHOXY-2-PROPANOL	ACGIH	TWA	100 ppm	
1-METHOXY-2-PROPANOL	ACGIH	STEL	150 ppm	
1-METHOXY-2-PROPANOL	OSHA	TWA	100 ppm	Table Z-1A
1-METHOXY-2-PROPANOL	OSHA	STEL	150 ppm	Table Z-1A
TRIETHANOLAMINE	ACGIH	TWA	5 mg/m3	

### SOURCE OF EXPOSURE LIMIT DATA:

ACGIH: American Conference of Governmental Industrial Hygienists

CMRG: Chemical Manufacturer Recommended Guideline

OSHA: Occupational Safety and Health Administration

AIHA: American Industrial Hygiene Association Workplace Environmental Exposure Level (WEEL)

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

<b>Specific Physical Form:</b>	Gel
<b>Odor, Color, Grade:</b>	Off-white viscous liquid with a fragrance
<b>General Physical Form:</b>	Liquid
<b>Autoignition temperature</b>	<i>No Data Available</i>
<b>Flash Point</b>	<i>Not Applicable</i>
<b>Flammable Limits - LEL</b>	<i>Not Applicable</i>
<b>Flammable Limits - UEL</b>	<i>Not Applicable</i>
<b>Boiling point</b>	212 °F
<b>Density</b>	1 g/ml
<b>Vapor Density</b>	<i>No Data Available</i>
<b>Vapor Pressure</b>	<=27 psia [@ 131 °F]

Specific Gravity	Approximately 1 [Ref Std: WATER=1]
pH	7.5 - 8.5
Melting point	No Data Available
Solubility in Water	Complete
Evaporation rate	No Data Available
Volatile Organic Compounds	2.78 % [Test Method: calculated SCAQMD rule 443.1] [Details: excluding exempt compounds]
Volatile Organic Compounds	27.93 g/l [Test Method: calculated SCAQMD rule 443.1] [Details: excluding exempt compounds]
Percent volatile	No Data Available
VOC Less H2O & Exempt Solvents	152.19 g/l [Test Method: calculated SCAQMD rule 443.1]
Viscosity	>=40,000 centipoise [Test Method: Brookfield]

**SECTION 10: STABILITY AND REACTIVITY**

**Stability:** Stable.

**Materials and Conditions to Avoid:** None known

**Hazardous Polymerization:** Hazardous polymerization will not occur.

**Hazardous Decomposition or By-Products**

<u>Substance</u>	<u>Condition</u>
Carbon monoxide	Not Specified
Carbon dioxide	Not Specified

**SECTION 11: TOXICOLOGICAL INFORMATION**

Please contact the address listed on the first page of the MSDS for Toxicological Information on this material and/or its components.

**SECTION 12: ECOLOGICAL INFORMATION**

**ECOTOXICOLOGICAL INFORMATION**

Not determined.

**CHEMICAL FATE INFORMATION**

Not determined.

**SECTION 13: DISPOSAL CONSIDERATIONS**

**Waste Disposal Method:** Incinerate in a permitted hazardous waste incinerator in the presence of a combustible material. As a

disposal alternative, dispose of waste product in a permitted hazardous waste facility.

EPA Hazardous Waste Number (RCRA): D018 (Benzene)

Since regulations vary, consult applicable regulations or authorities before disposal.

## SECTION 14: TRANSPORT INFORMATION

**ID Number(s):**

LB-T100-0387-1, 60-9801-0630-0

Please contact the emergency numbers listed on the first page of the MSDS for Transportation Information for this material.

## SECTION 15: REGULATORY INFORMATION

### US FEDERAL REGULATIONS

Contact 3M for more information.

**311/312 Hazard Categories:**

Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No Immediate Hazard - Yes Delayed Hazard - No

### STATE REGULATIONS

Contact 3M for more information.

### CHEMICAL INVENTORIES

The components of this product are in compliance with the chemical notification requirements of TSCA.

All applicable chemical ingredients in this material are listed on the European Inventory of Existing Chemical Substances (EINECS), or are exempt polymers whose monomers are listed on EINECS.

Contact 3M for more information.

### INTERNATIONAL REGULATIONS

Contact 3M for more information.

**WHMIS:** Hazardous

This MSDS has been prepared to meet the U.S. OSHA Hazard Communication Standard, 29 CFR 1910.1200.

## SECTION 16: OTHER INFORMATION

### NFPA Hazard Classification

**Health:** 2 **Flammability:** 1 **Reactivity:** 0 **Special Hazards:** None

National Fire Protection Association (NFPA) hazard ratings are designed for use by emergency response personnel to address the hazards that are presented by short-term, acute exposure to a material under conditions of fire, spill, or similar emergencies. Hazard ratings are primarily based on the inherent physical and toxic properties of the material but also include the toxic properties of combustion or decomposition products that are known to be generated in significant quantities.

### HMIS Hazard Classification

**Health:** 2 **Flammability:** 1 **Reactivity:** 0 **Protection:** A

Hazardous Material Identification System (HMIS(r)) hazard ratings are designed to inform employees of chemical hazards in the workplace. These ratings are based on the inherent properties of the material under expected conditions of normal use and are not intended for use in emergency situations. HMIS(r) ratings are to be used with a fully implemented HMIS(r) program. HMIS(r) is a registered mark of the National Paint and Coatings Association (NPCA).

**Reason for Reissue:** Updating MSDS

### Revision Changes:

Section 1: Product use information was modified.  
Copyright was modified.  
Section 3: Potential effects from skin contact information was modified.  
Section 5: Extinguishing media information was modified.  
Section 5: Unusual fire and explosion hazard information was modified.  
Section 6: Release measures information was modified.  
Section 7: Handling information was modified.  
Section 8: Skin protection phrase was modified.  
Section 10: Hazardous decomposition or by-products table was modified.  
Section 13: Waste disposal method comment was deleted.  
Section 8: Eye/face protection information was added.  
Section 8: Skin protection - recommended gloves information was added.  
Section 8: Eye/face protection text was added.  
Section 8: Skin protection - recommended gloves text was added.  
Section 3: Other health effects information was modified.  
Section 15: Inventories information was modified.  
Section 9: Density information was modified.  
Section 9: Boiling point information was modified.  
Sections 3 and 9: Odor, color, grade information was modified.  
Section 9: Property description for optional properties was modified.  
Section 8: Skin protection - protective clothing text was added.  
Section 8: Eye/face protection information - punctuation - was added.  
Section 8: Skin protection - recommended gloves - punctuation was added.  
Section 14: ID Number Heading Template 1 was added.  
Section 14: ID Number(s) Template 1 was added.  
Section 2: Ingredient table was added.  
Section 8: Exposure guidelines ingredient information was added.  
Section 8: Exposure guidelines data source legend was added.

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. 3M MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

3M provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from 3M.

**3M MSDSs are available at [www.3M.com](http://www.3M.com)**