

# **Material Safety Data Sheet**

E-6000 WATER BASED SPRAY APPLIED ADHESIVE

## 1. Product and company identification

Product name : E-6000 WATER BASED SPRAY APPLIED ADHESIVE

**Supplier**: Eclectic Products Inc.

1075 Arrowsmith Eugene, OR 97402 541-484-9621

Material uses : Consumer products: Adhesive.

**Manufacturer** : Eclectic Products Inc.

1075 Arrowsmith Eugene, OR 97402 541-484-9621

 Code
 : 1000354

 Validation date
 : 4/10/2013.

 Print date
 : 4/10/2013.

Responsible name : Regulatory Compliance In case of emergency : Eclectic Products Inc.

1075 Arrowsmith Eugene, OR 97402 541-484-9621

## 2. Hazards identification

Physical state : Liquid.

Emergency overview : MAY CAUSE RESPIRATORY TRACT, EYE AND SKIN IRRITATION.

Slightly irritating to the eyes, skin and respiratory system. Avoid breathing vapor or mist. Avoid contact with eyes. Avoid prolonged or repeated contact with skin. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for

use. Wash thoroughly after handling.

Routes of entry : Dermal contact. Eye contact. Inhalation.

#### Potential acute health effects

Inhalation : Slightly irritating to the respiratory system.

Ingestion : No known significant effects or critical hazards.

Skin : Slightly irritating to the skin.

Eyes : Slightly irritating to the eyes.

#### Potential chronic health effects

Chronic effects
 Carcinogenicity
 Mutagenicity
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.
 Teratogenicity
 No known significant effects or critical hazards.
 Developmental effects
 No known significant effects or critical hazards.
 Fertility effects
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

#### Over-exposure signs/symptoms

Inhalation : Adverse symptoms may include the following:

respiratory tract irritation

coughing

Ingestion : No specific data.

**Skin**: Adverse symptoms may include the following:

irritation redness

4/10/2013.

## 2. Hazards identification

**Eyes** 

: Adverse symptoms may include the following:

irritation watering redness

Medical conditions aggravated by overexposure : None known.

See toxicological information (section 11)

## 3. Composition/information on ingredients

Name

Propylene Glycol

Strict Stric

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. First aid measures

**Eye contact** 

: Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact

: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation

Move exposed person to fresh air. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion

Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get medical attention immediately.

**Protection of first-aiders** 

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation.

Notes to physician

No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

## 5. Fire-fighting measures

Flammability of the product

: In a fire or if heated, a pressure increase will occur and the container may burst.

**Extinguishing media** 

Suitable

: Use an extinguishing agent suitable for the surrounding fire.

Not suitable

None known.

carbon monoxide

Special exposure hazards

: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Hazardous combustion products

: Decomposition products may include the following materials: carbon dioxide

Special protective equipment for fire-fighters

: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

4/10/2013. 2/7

### 6. Accidental release measures

#### **Personal precautions**

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment (see section 8).

#### **Environmental precautions**

: Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Large spill

Extra leak if without risk. Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Contaminated absorbent material may pose the same hazard as the spilled product. Note: see section 1 for emergency contact information and section 13 for waste disposal.

#### **Small spill**

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

## 7. Handling and storage

#### **Handling**

• Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.

#### **Storage**

: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

## 8. Exposure controls/personal protection

**Product name** 

ropylene Glycol

**Exposure limits** 

AIHA WEEL (United States, 5/2010). Notes: 2004 Revised Document TWA: 10 mg/m³ 8 hour(s).

# Recommended monitoring procedures

: If this product contains ingredients with exposure limits, personal, workplace atmosphere or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment.

#### **Engineering measures**

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

#### **Hygiene measures**

: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

#### **Personal protection**

Respiratory

: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

4/10/2013. 3/7

### 8. Exposure controls/personal protection

Hands

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

Eyes

: Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Skin

Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.

Environmental exposure controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

# 9. Physical and chemical properties

Physical state : Liquid.

Flash point : Not available.

Color : White.
Odor : Odorless.

**Boiling/condensation point** : >100°C (>212°F)

 Specific gravity
 : ₹.05

 Estimated Vapor Density
 : >1 [Air = 1]

 VOC %
 : ₹.00577%

 Evaporation rate
 : <1 (Water = 1)</td>

**Solubility** : Easily soluble in the following materials: water.

## 10. Stability and reactivity

Stability

: The product is stable.

Conditions to avoid

No specific data.

**Materials to avoid** 

No specific data.

Hazardous decomposition

No specific data.
 Under normal conditions of storage and use, hazardous decomposition products should

products

not be produced.

Hazardous polymerization

.... Do p. od a.oo a.

Conditions of reactivity

Under normal conditions of storage and use, hazardous polymerization will not occur.Non-flammable in the presence of the following materials or conditions: open flames,

 Non-flammable in the presence of the following materials or conditions: op sparks and static discharge and heat.

## 11. Toxicological information

#### **Acute toxicity**

Product/ingredient name
Propylene Glycol

Result LD50 Dermal LD50 Intramuscular	Species Rabbit Rat	<b>Dose</b> 20800 mg/kg 14 g/kg	Exposure -
LD50 Intramuscular	Rat	20000 mg/kg	-
LD50 Intraperitoneal	Rat	6660 mg/kg	-
LD50 Intravenous	Rat	6800 mg/kg	-
LD50 Intravenous	Rat	6423 mg/kg	-
LD50 Oral	Rat	20 g/kg	-
LD50 Subcutaneous	Rat	28000 mg/kg	-
LD50 Subcutaneous	Rat	22500 mg/kg	-
TDLo	Rat	19500 mg/kg	-

4/10/2013. 4/7

## 11. Toxicological information

Intraperitoneal

**Carcinogenicity** 

**Conclusion/Summary** 

IDLH : Not available.Synergistic products : Not available.

# 12. Ecological information

**Environmental effects**: No known significant effects or critical hazards.

**Aquatic ecotoxicity** 

Product/ingredient name Propylene Glycol	Test -	Result Acute EC50 >1000 mg/L Fresh water	Species Daphnia - Water flea - Daphnia magna - <24	<b>Exposure</b> 48 hours
	-	Acute EC50 >10000000 ug/L Fresh water	hours Daphnia - Water flea - Daphnia magna - 6 to 24 hours	48 hours
	-	Acute LC50 34060 mg/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <=7 days	96 hours
	-	Acute LC50 15052 mg/L Fresh water	Crustaceans - Water flea - Ceriodaphnia dubia - <24 hours	48 hours
	-	Acute LC50 5122 mg/L Fresh water	Crustaceans -	48 hours
	-	Acute LC50 4919 mg/L Fresh water	Crustaceans - Water flea - Ceriodaphnia dubia - <24 hours	48 hours
	-	Acute LC50 >1000 mg/L Marine water	Crustaceans - Amphipod - Chaetogammarus marinus - Young - 5 mm	48 hours
	-	Acute LC50 44 ml/L Fresh water	Fish - Rainbow trout,donaldson trout - Oncorhynchus mykiss - 0.8 g	96 hours
	-	Acute LC50 55770000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <=7 days	96 hours
	-	Acute LC50 1020000 ug/L Fresh water	Crustaceans - Water flea - Ceriodaphnia dubia - <24 hours	48 hours
	-	Acute LC50 710000 ug/L Fresh water	Fish - Fathead minnow - Pimephales promelas - <=7 days	96 hours

**Conclusion/Summary** : Not available.

4/10/2013. 5/7

## 12. Ecological information

**Biodegradability** 

**Conclusion/Summary**: Not available.

## 13. Disposal considerations

**Waste disposal** 

: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any byproducts should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Refer to Section 7: HANDLING AND STORAGE and Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for additional handling information and protection of employees.

## 14. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated.	-	-	-		-
TDG Classification	Not regulated.	-	-	-		-
IMDG Class	Not regulated.	-	-	-		-
IATA-DGR Class	Not regulated.	-	-	-		-

PG\*: Packing group

## 15. Regulatory information

U.S. Federal regulations : TSCA 8(b) inventory: All components are listed or exempted.

SARA 311/312 - Acute

**Canada** 

WHMIS (Canada)
: Not controlled under WHMIS (Canada).

**Canada inventory** : All components are listed or exempted.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all the information required by the CPR.

**Mexico** 

Classification :



**EU regulations** 

Risk phrases : This product is not classified according to EU legislation.

**International regulations** 

4/10/2013. 6/7

## 15. Regulatory information

International lists : Australia inventory (AICS): All components are listed or exempted.

China inventory (IECSC): Not determined.

Japan inventory: All components are listed or exempted.

Korea inventory: Not determined.

New Zealand Inventory of Chemicals (NZIoC): Not determined.

Philippines inventory (PICCS): All components are listed or exempted.

: At least one component is not listed in EINECS but all such components are listed in


ELINCS.

Please contact your supplier for information on the inventory status of this material.

### 16. Other information

Hazardous Material Information System (U.S.A.)

**EU Inventory** 



Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868.

The customer is responsible for determining the PPE code for this material.

National Fire Protection Association (U.S.A.)



Date of printing : 4/10/2013.

Date of issue : 4/10/2013.

Date of previous issue : 10/15/2012.

Version : 1.01

✓ Indicates information that has changed from previously issued version.

#### **Notice to reader**

To the best of our knowledge, the information contained herein is accurate. However, neither the above-named supplier, nor any of its subsidiaries, assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

4/10/2013. 7/7