

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ULTRA-GLO HARDENER

Page1

of 4

PRODUCT CLASS: CLEAR EPOXY HARDENER

D.O.T. SHIPPING INFORMATION:

PRODUCT NUMBER: 00078 PART H

PROPER SHIPPING NAME: CONSUMER

COMMODITY

SECTION I

PROPER HAZARD CLASS: ORM-D

ENVIRONMENTAL TECHNOLOGY, INC.

300 SOUTH BAY DEPOT ROAD

FIELDS LANDING, CA 95537

PHONE NUMBER FOR INFORMATION: (707) 443-9323

TRANSPORTATION EMERGENCY

PHONE NUMBER:

CHEMTREC (800) 424-9300

DATE PREPARED: 09/06/08

PREPARED BY: TECHNICAL DEPARTMENT

SECTION II Hazardous Ingredients/Identity Information

HAZARDOUS COMPONENTS	CAS REG.NO.	APPR OX WT. %	ACGIH TWA/TL V	OSHA PEL	VAPOR PRESSUR E mm Hg
NONYL PHENOL	84852-15-3	T/S	N/E	N/E	<1
N-AMINOETHYLPIPERAZINE	140318	T/S	N/E	N/E	0.05
POLYOXYALKYLENEAMINES	T/S	T/S	N/E	N/E	N/E

Although no exposure standards have been established for this product, air contaminant concentrations must

be maintained at lowest possible levels. T/S = TRADE SECRET N/A = NOT AVAILABLE N/E = NOT ESTABLISHED

SECTION III - Physical/Chemical Characteristics

BOILING RANGE °F	>400	PERCENT VOLATILE BY VOLUME		T/S
MELTING OR FREEZING POINT	N/E	PERCENT VOLATILE BY WEIGHT		T/S
VAPOR DENSITY (AIR=1)	>1	EVAPORATION RATE (SLOWER THAN ETHER)	LBS./GAL	8.1
SOLUBILITY IN WATER: SLIGHT			VOC LBS/GAL	T/S
APPEARANCE AND ODOR: CLEAR, SLIGHTLY YELLOW, SOMEWHAT VISCOUS SOLUTION WITH TYPICAL AMINE ODOR (SOMEWHAT FISHY)			VOC GRAMS/LITER	T/S

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): >200°F PMCC FLAMMABLE LIMITS: LEL: N/E UEL: N/E

EXTINGUISHING MEDIA: ☒ FOAM ☒ ALCOHOL FOAM ☒ CO₂ ☒ DRY CHEMICAL ☒ WATER SPRAY ☐ OTHER

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ULTRA-GLO HARDENER

Page2

of 4

SPECIAL FIRE FIGHTING PROCEDURES: USE NIOSH APPROVED PROTECTIVE CLOTHING INCLUDING POSITIVE PRESSURE SELF CONTAINED BREATHING APPARATUS(SCBA). COOL UNOPENED CONTAINERS WITH WATER SPRAY. UNUSUAL FIRE AND EXPLOSION HAZARDS: NONE EXPECTED

SECTION V - REACTIVITY DATA

STABILITY ☐ UNSTABLE ☒ STABLE / CONDITIONS TO AVOID:

INCOMPATIBILITY (MATERIALS TO AVOID): ACIDS OR POLYMERS REACTIVE WITH AMINES

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: BURNING PRODUCT WILL EMIT TOXIC OXIDES OF CARBON AND NITROGEN.

HAZARDOUS POLYMERIZATION ☐ MAY OCCUR ☒ MAY NOT OCCUR. CONDITIONS TO AVOID: AVOID PRODUCT CONTAMINATION.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ULTRA-GLO HARDENER

Page3

of 4

SECTION VI - HEALTH HAZARD DATA

ROUTE(S) OF ENTRY: INHALATION? YES SKIN? YES INGESTION? NOT LIKELY

HEALTH HAZARDS (ACUTE AND CHRONIC): DANGER - MATERIAL IS CORROSIVE AND COULD SEVERELY BURN SKIN, EYES, RESPIRATORY TRACT, AND LUNGS IF ASPIRATED. COULD CAUSE BLINDNESS OR DEATH IF SWALLOWED.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO
SIGNS AND SYMPTOMS OF EXPOSURE: IRRITATION OF EYES, SKIN AND RESPIRATORY SYSTEM. CAUSES PAIN IN EXPOSED AREAS; BLISTERS MAY FORM, ABDOMINAL AND DIGESTIVE TRACT PAIN IF SWALLOWED.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE: PRE-EXISTING SKIN AND/OR RESPIRATORY PROBLEMS COULD BE WORSENER BY EXPOSURE TO THIS PRODUCT.

EMERGENCY AND FIRST AID PROCEDURES: FLUSH EYES WITH RUNNING WATER AT LEAST 15 MINUTES. REMOVE CONTAMINATED CLOTHING; WASH SKIN WITH WARM, SOAPY WATER, THEN RINSE WELL. IF INGESTED, DO NOT INDUCE VOMITING. FOR ANY SIGNIFICANT EXPOSURE, CONTACT A POISON CONTROL CENTER IMMEDIATELY.

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: VENTILATE AREA. WEAR PROTECTIVE CLOTHING AND NIOSH APPROVED RESPIRATOR. DIKE AND CONTAIN SPILL. SPREAD ABSORBENT MATERIAL. KEEP SPECTATORS AWAY.

WASTE DISPOSAL METHOD: NOT A RCRA HAZARDOUS WASTE AS SUPPLIED; USER MUST DETERMINE RCRA STATUS AT TIME OF DISPOSAL. LANDFILL OR INCINERATE IN ACCORDANCE WITH EXISTING FEDERAL, STATE, AND LOCAL REGULATIONS.

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: STORE IN COOL DRY AREA, AWAY FROM STRONG OXIDANTS, HEAT OR IGNITION SOURCES. ALWAYS KEEP CONTAINERS CLOSED. DO NOT GET ON SKIN OR BREATHE VAPORS.

OTHER PRECAUTIONS: CLEAN UP ANY SPILLS IMMEDIATELY. WASH ANY AREAS OF BODY CONTACT IMMEDIATELY.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION (SPECIFY TYPE): NIOSH APPROVED TO PREVENT INHALATION OF VAPORS; IF VENTILATION IS INADEQUATE, SCBA MAY BE REQUIRED.

VENTILATION: LOCAL EXHAUST: IF REQUIRED. SPECIAL VENTILATION MUST BE ADEQUATE TO AVOID BREATHING VAPORS.

USE IN SEALED EQUIPMENT AS MUCH AS POSSIBLE. MECHANICAL (GENERAL): REQUIRED

PROTECTIVE GLOVES: NEOPRENE OR RUBBER EYE PROTECTION: SAFETY GOGGLES

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: TO AVOID ALL SKIN CONTACT, WEAR A PROTECTIVE APRON AND AVOID FOOT CONTACT.

WORK/HYGIENIC PRACTICES: WASH AT END OF WORK SHIFT, BEFORE EATING, SMOKING OR USING RESTROOM. DO NOT RE-USE CONTAMINATED CLOTHING.

MATERIAL SAFETY DATA SHEET

PRODUCT NAME: ULTRA-GLO HARDENER

Page4

of 4

REGULATORY INFORMATION: THIS PRODUCT IS REGULATED UNDER SARA TITLE III SECTION 311 AS ACUTELY HAZARDOUS.

All information, recommendations, and suggestions appearing herein concerning our product are based upon tests and data believed to be reliable. However, it is the user's responsibility to determine the safety, toxicity, and suitability for his or her own use of the product described herein. Since the actual use by others is beyond Environmental Technology, Inc.'s control, no guarantee, expressed or implied, is made by Environmental Technology, Inc. as to the effects of such use, the results to be obtained, or the safety and toxicity of the product.