

1 Identification

- Product identifier

- **Trade name:** Mr. Sticky's Underwater Glue
- **Synonyms:** Underwater Glue - Part B
- **Part number:** 001327
- **Application of the substance / the mixture** Adhesives

- Details of the supplier of the safety data sheet

- **Manufacturer/Supplier:**
Advanced Adhesion, Inc
8004 California Avenue
Fair Oaks, Ca 95628
USA
Telephone: +1 916-961-4700
Email: info@mrstickys.com
Website: www.mrstickys.com
- **Information department:** Product safety department
- **Emergency telephone number:**
United States: 1-916-961-4700
International: +1-916-961-4700

* 2 Hazard(s) identification

- Classification of the substance or mixture



GHS08 Health hazard

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS05 Corrosion

Skin Corr. 1B H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

- Label elements

- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

- Hazard pictograms



GHS05 GHS07 GHS08

- Signal word

- Hazard-determining components of labeling:

Poly(acrylonitrile-co-butadiene), Amine Terminated
Epoxy curing agent
Nonylphenol
Dinonyl phenol
triethylenetetramine

- Hazard statements

H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H361 Suspected of damaging fertility or the unborn child.

- Precautionary statements

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dusts or mists.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P264 Wash face, hands and any exposed skin thoroughly after handling.

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Mr. Sticky's Underwater Glue

(Contd. of page 1)

- Precautionary statements

- P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P261 Avoid breathing dust/fume/gas/mist/vapors/spray
 P264 Wash face, hands and any exposed skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing must not be allowed out of the workplace.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P280 Wear protective gloves.
 P280 Wear eye protection / face protection.
 P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a poison center/doctor.
 P308+P313 IF exposed or concerned: Get medical advice/attention.
 P321 Specific treatment (see on this label).
 P312 Call a poison center/doctor if you feel unwell.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.
 P403+P233 Store in a well-ventilated place. Keep container tightly closed.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Classification system:

- NFPA ratings (scale 0 - 4)



- HMIS-ratings (scale 0 - 4)



- Other hazards

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

* 3 Composition/information on ingredients

- Chemical characterization: Mixtures

- **Description:** Mixture of the substances listed below with nonhazardous additions.

- Dangerous components:

CAS: 25068-38-6	Bisphenol-A epoxy resin	50 – 59%
	Skin Sens. 1, H317; STOT SE 3, H335	
CAS: 471-34-1	calcium carbonate	10 – 19%
CAS: 1323-65-5	Dinonyl phenol	10 – 19%
	Eye Dam. 1, H318; Skin Irrit. 2, H315	
	Modified epoxy resin	10 – 19%
	Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Skin Sens. 1B, H317	
CAS: 67762-90-7	Amorphous Silica	5 – 9%
	Combustible Dust	
CAS: 84852-15-3	Nonylphenol	4.023%
	Repr. 2, H361; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302	
CAS: 13463-67-7	titanium dioxide	1 – 4%
	Carc. 2, H351	

* 4 First-aid measures

- Description of first aid measures

- After inhalation:

Supply fresh air and to be sure call for a doctor.
 In case of unconsciousness place patient stably in side position for transportation.
 Supply fresh air; consult doctor in case of complaints.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Mr. Sticky's Underwater Glue

(Contd. of page 2)

- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed** No further relevant information available.
 - **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:**
CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
CO2, sand, extinguishing powder. Do not use water.
Use fire fighting measures that suit the environment.
 - **For safety reasons unsuitable extinguishing agents:** Water
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
 - **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
Ensure adequate ventilation
Wear protective clothing.
- **Environmental precautions:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
Dispose of the collected material according to regulations.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

* 7 Handling and storage

- **Handling:**
 - **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
 - **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
 - **Storage:**
 - **Requirements to be met by storerooms and receptacles:** No special requirements.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** None.
- **Specific end use(s)** No further relevant information available.

* 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
 - **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

CAS: 471-34-1 calcium carbonate

PEL	Long-term value: 15* 5** mg/m ³ *total dust **respirable fraction
REL	Long-term value: 10* 5** mg/m ³ *total dust **respirable fraction
TLV	TLV withdrawn

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Mr. Sticky's Underwater Glue

(Contd. of page 3)

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the skin.
Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
Nitrile rubber, NBR

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **As protection from splashes gloves made of the following materials are suitable:** Nitrile rubber, NBR

- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

* 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

- **Form:** Pasty
- **Color:** Grey
- **Odor:** Characteristic
- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

- **Melting point/Melting range:** Undetermined.
- **Boiling point/Boiling range:** $\geq 260\text{ }^{\circ}\text{C}$ ($\geq 500\text{ }^{\circ}\text{F}$)

- **Flash point:** $145\text{ }^{\circ}\text{C}$ ($293\text{ }^{\circ}\text{F}$)

- **Flammability (solid, gaseous):** Not applicable.

- **Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

- **Lower:** Not determined.
- **Upper:** Not determined.

- **Vapor pressure:** Not determined.

- **Density at $20\text{ }^{\circ}\text{C}$ ($68\text{ }^{\circ}\text{F}$):** $\sim 1.45469\text{ g/cm}^3$ ($\sim 12.13939\text{ lbs/gal}$)

- **Relative density:** Not determined.
- **Vapor density:** Not determined.
- **Evaporation rate:** Not determined.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Mr. Sticky's Underwater Glue

(Contd. of page 4)

- Solubility in / Miscibility with	
- Water:	Not miscible or difficult to mix.
- Partition coefficient (n-octanol/water): Not determined.	
- Viscosity:	
- Dynamic at 20 °C (68 °F):	750,000 mPas
- Kinematic:	Not determined.
- Solvent content:	
- VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
- Solids content:	23.5 %
- Other information No further relevant information available.	

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
 - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

*11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- LD/LC50 values that are relevant for classification:		
ATE (Acute Toxicity Estimate)		
Oral	LD50	12,741 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rat)
Inhalative	LC50/4 h	> 673 mg/l (rat)
CAS: 471-34-1 calcium carbonate		
Oral	LD50	6,450 mg/kg (rat)
Modified epoxy resin		
Oral	LD50	2,000 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rat)
CAS: 84852-15-3 Nonylphenol		
Oral	LD50	1,412 mg/kg (rat)
CAS: 13463-67-7 titanium dioxide		
Oral	LD50	> 20,000 mg/kg (rat)
Dermal	LD50	> 10,000 mg/kg (rabbit)
Inhalative	LC50/4 h	> 6.82 mg/l (rat)

- **Primary irritant effect:**
 - **on the skin:** Irritant to skin and mucous membranes.
 - **on the eye:** Strong irritant with the danger of severe eye injury.
- **Sensitization:** Sensitization possible through skin contact.

- Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- Carcinogenic categories

- IARC (International Agency for Research on Cancer)	
CAS: 13463-67-7 titanium dioxide	2B
- NTP (National Toxicology Program)	
None of the ingredients is listed.	
- OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Mr. Sticky's Underwater Glue

(Contd. of page 5)

12 Ecological information






- **Toxicity**
 - **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
 - **Bioaccumulative potential** No further relevant information available.
 - **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
 - **Remark:** Toxic for fish
- **Additional ecological information:**
 - **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
 - **PBT:** Not applicable.
 - **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
 - **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
 - **Recommendation:** Disposal must be made according to official regulations.

* 14 Transport information

- UN-Number - DOT, IMDG, IATA		UN1760
- UN proper shipping name - DOT - IMDG - IATA		Corrosive liquids, n.o.s. (Phenol, 4-nonyl-, branched, Dinonylphenol, Nonylphenol) CORROSIVE LIQUID, N.O.S. (Phenol, 4-nonyl-, branched, Dinonylphenol, Nonylphenol), MARINE POLLUTANT CORROSIVE LIQUID, N.O.S. (Phenol, 4-nonyl-, branched, Dinonylphenol, Nonylphenol)
- Transport hazard class(es) - DOT   - Class - Label		8 Corrosive substances 8
- IMDG   - Class - Label		8 Corrosive substances 8
- IATA  - Class - Label		8 Corrosive substances 8

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Mr. Sticky's Underwater Glue

(Contd. of page 6)

- Packing group - DOT, IMDG, IATA	II
- Environmental hazards: - Marine pollutant:	Product contains environmentally hazardous substances: Nonylphenol Yes Symbol (fish and tree)
- Special precautions for user - Danger code (Kemler): - EMS Number: - Stowage Category - Stowage Code	Warning: Corrosive substances 80 F-A,S-B B SW2 Clear of living quarters.
- Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
- Transport/Additional information: - DOT - Quantity limitations - Remarks:	 On passenger aircraft/rail: 1 L On cargo aircraft only: 30 L Special marking with the symbol (fish and tree).
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN 1760 CORROSIVE LIQUID, N.O.S. (PHENOL, 4-NONYL-, BRANCHED, DINONYLPHENOL, NONYLPHENOL), 8, II

*15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

CAS: 84852-15-3 | Nonylphenol

- **TSCA (Toxic Substances Control Act):**

Bisphenol-A epoxy resin
calcium carbonate
Dinonyl phenol
Amorphous Silica
Nonylphenol
titanium dioxide
Silane
Alumina Trihydrate

- **TSCA new (21st Century Act): (Substances not listed)**

Modified epoxy resin

- **Hazardous Air Pollutants**

None of the ingredients is listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/06/2019

Reviewed on 03/05/2019

Trade name: Mr. Sticky's Underwater Glue

(Contd. of page 7)

- Carcinogenic categories

- EPA (Environmental Protection Agency)

None of the ingredients is listed.

- TLV (Threshold Limit Value established by ACGIH)

CAS: 13463-67-7 titanium dioxide

A4

- NIOSH-Ca (National Institute for Occupational Safety and Health)

CAS: 13463-67-7 titanium dioxide

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** ND Industries, Inc. - Safety, Health and Environmental Affairs

- **Contact:** Safety, Health and Environmental Affairs

- **Date of preparation / last revision** 03/06/2019 / 22

- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 DOT: US Department of Transportation
 IATA: International Air Transport Association
 ACGIH: American Conference of Governmental Industrial Hygienists
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 NFPA: National Fire Protection Association (USA)
 HMIS: Hazardous Materials Identification System (USA)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 vPvB: very Persistent and very Bioaccumulative
 NIOSH: National Institute for Occupational Safety
 OSHA: Occupational Safety & Health
 TLV: Threshold Limit Value
 PEL: Permissible Exposure Limit
 REL: Recommended Exposure Limit
 Acute Tox. 4: Acute toxicity – Category 4
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B
 Skin Irrit. 2: Skin corrosion/irritation – Category 2
 Eye Dam. 1: Serious eye damage/eye irritation – Category 1
 Skin Sens. 1: Skin sensitisation – Category 1
 Skin Sens. 1B: Skin sensitisation – Category 1B
 Carc. 2: Carcinogenicity – Category 2
 Repr. 2: Reproductive toxicity – Category 2
 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

- * **Data compared to the previous version altered.**

- Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated,
 ®Vibra-TITE is a registered trademark of ND Industries, Inc.