

Revision Date: 02/26/2007

Print Date: 2/28/2007 MSDS Number: R0371467

Version: 1.2

KNTPCSM CDM1808GB 50" KNYTEX 23332

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Ashland Regulatory Information Number
P.O. Box 2219 Telephone

Columbus, OH 43216 Emergency telephone number

1-800-ASHLAND (1-800-274-5263)

1-800-325-3751

614-790-3333

Product name KNIT/CSM CDM1808GB 50" KNYTEX

Product code 23332
Product Use Description No data

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: solid, White

Moderate skin initant.

Potential Health Effects

Routes of exposure

Inhalation, Skin contact, Eye Contact

Eye contact

Fibrous glass or its dust may cause eye irritation from the material scratching the eyes. Symptoms include itching, stinging, tearing, redness, and swelling of eyes.

Skin contact

Contact with fibrous glass or its dust can cause skin irritation. Symptoms may include redness and an itchy, sometimes bumpy, rash. The rash is aggravated by rubbing or scratching which may even force the glass fibers into the skin. With repeated exposure, some individuals will develop a hardening of the skin and a resistance to the irritant effects of the fibers. Skin irritation is common in individuals newly exposed to fibrous glass.

Ingestion

This material is not likely to be swallowed.

Inhalation



Revision Date: 02/26/2007

Print Date: 2/28/2007 MSDS Number: R0371467

ber: R0371467 Version: 1.2

KNIT/CSM CDM1808GB 50" KNYTEX 23332

Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.). Breathing of glass fibers can cause short-term irritation of the mouth, nose, and throat. Other symptoms may include coughing and wheezing. Because of the structure of the fibers, they do not enter the lungs (See Other Health Effects).

Aggravated Medical Condition

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:, skin, lung (for example, asthma-like conditions)

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:, mouth and throat irritation (soreness, dry or scratchy feeling, cough), irritation (nose, throat, airways)

Target Organs

No data

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA)., Studies with workers employed up to 40 years in the manufacture of fiberglass have shown no increase in cancer due to liberglass exposure. Breathing continuous filament fiberglass did not cause cancer in laboratory animals. Studies using artificial implantation or injection of glass fibers into animals have resulted in cancer. Those studies are not considered relevant to human exposure.

Reproductive hazard.

There are no data available for assessing risk to the fetus from maternal exposure to this material.

Other information

Continuous filament fiber glass is a type of man-made mineral fiber. Fiber diameter is the most important factor in determining whether or not fibers can get into the lungs if breathed. Fibers that can enter the lungs are called respirable fibers. According to the National Institute for Occupational Safety and Health (NIOSH), fibers with diameters greater than 3.5 microns are not respirable. This product is composed of glass strands with diameters greater than 3.5 microns, and therefore, if breathed, would not enter the lungs. Instead, they would be stopped in the upper respiratory tract where they would be removed by natural mechanisms such as filtering by nasal hairs. Continuous filament fiber glass products that are chopped, crushed, or severely mechanically



Revision Date: 02/26/2007

Print Date: 2/28/2007 MSDS Number: R0371467

Version: 1.2

KNIT/CSM CDM1808GB 50" KNYTEX 23332

processed during manufacturing or use may contain a very small amount of respirable fibers that could reach the deep lung. The measured airborne concentration of these respirable fibers in areas where severe processing of fiberglass occurred has been shown to be extremely low and well below the TLV. Repeated or prolonged exposure to respirable glass fibers has caused fibrosis, lung cancer and mesothelioma in long-term studies in laboratory animals.

3. COMPOSITION/INFORMATION ON INCREDIENTS

Components	CAS-No.	Concentration
GLASS	NJTS# 800986-	<=100%
	5523P	

4. FIRST AID MEASURES

Eyes

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding cyclids apart; seek immediate medical attention.

Skin

Wash contacted areas with mild soap and running water. Use a washeloth to help remove fibers. Do not rub or scratch affected areas since this can force fibers into the skin. Seek medical attention if irritation persists. Remove material from clothing using vacuum equipment (never use compressed air). Wash work clothing separately from other clothing before reuse. Wipe out the washer or sink to prevent loose glass fibers from getting on other clothing.

Ingestion

First aid is not normally required. If symptoms develop, seek medical attention.

Inhalation

First aid is not normally required. If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention.

Notes to physician

Hazards: No information available.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES



Revision Date: 02/26/2007

Print Date: 2/28/2007 MSDS Number: R0371467

Version: 1.2

KNIT/CSM CDM1808GB 50" KNYTEX 23332

Suitable extinguishing media

dry chemical, foam, water spray, carbon dioxide (CO2)

Hazardous combustion products

In a sustained fire, sizing and binders may decompose, releasing combustion products including carbon dioxide, carbon monoxide, various hydrocarbons, and water.

Precautions for fire-fighting

No special fire hazards are known to be associated with this product. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

No data

Environmental precautions

No data

Methods for cleaning up

Minimize dust. Sweep, shovel, or vacuum. Other information

Contain and handle as described for small spills. For very large spills, transfer spilled product into new containers.

7. HANDLING AND STORAGE

Handling

Secondary operations, such as grinding and sanding, may produce dust. Prevent dust formation. Keep the work area clean of dusts and fibers released during processing or fabrication. Use vacuum equipment to clean up product. Avoid dry sweeping or using compressed air as these techniques cause dust and fibers to reenter the air.

Storage

No data

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Guidelines



Revision Date: 02/26/2007

Print Date: 2/28/2007 MSDS Number: R0371467

Version: 1.2

KNIT/CSM CDM1808GB 50" KNYTEX 23332

FIBERGLASS	65997-17-3			
ACGIH	time weighted average	5 ing/m3	Inhalable fraction.	
NIOSH	Recommended exposure limit (REL):	5 mg/m3	Total dust.	
NIOSH	Recommended exposure limit (RBL):	5 mg/m3	Total	
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	5 mg/m3	Respirable fraction.	
US CA OFL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	10 mg/m3	Total dust.	

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below level of overexposure (from known, suspected or apparent adverse effects).

Eye protection

Wear safety glasses or goggles, resistant gloves, and other appropriate protective equipment essential for your operation.

Skin and body protection

Wear normal work clothing covering arms and legs.

Respiratory protection

3M Dust respirator No. 8710 or 9900 is recommended or a NIOSH-approved dust respirator. (See your safety equipment supplier.)

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	solid
Form	No data
Colour	White
Odour	No data
Boiling point/range	No data



Revision Date: 02/26/2007

Print Date: 2/28/2007 MSDS Number: R0371467

Version: 1.2

KNIT/CSM CDM1808GB 50* KNYTEX 23332

pH No dataFlash point No data

Evaporation rate No data
Explosion limits No data
Vapour pressure No data

Vapour density No data
No data

Density 2.560 g/cm³ @ 77.00 °F / 25.00 °C

No data

Solubility insoluble in water

Partition coefficient (n- No data

octanol/water)

Autoignition temperature No data

10. STABILITY AND REACTIVITY

Stability

Stable.

Conditions to avoid

None known.

Incompatible products

Avoid contact with:, None known,

Hazardous decomposition products

No data

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

Acute inhalation toxicity

Acute dermal toxicity



Revision Date: 02/26/2007

Print Date: 2/28/2007 MSDS Number: R0371467

Version: 1.2

KNIT/CSM CDM1808GB 50" KNYTEX 23332

12. ECOLOGICAL INFORMATION

Aquatic toxicity

Acute and Prolonged Toxicity to Flsh

No data

Acute Toxicity to Aquatic Invertebrates

No data

Environmental fate and pathways

No data

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. Dispose of with other normal, solid waste For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution Company, IC&S Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

Dangerous goods descriptions may not reflect package size, quantity, end-use or regionspecific exceptions that can be applied to shipments. Consult shipping documents for material-specific descriptions.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known in the State of California to cause cancer.

FIBERGLASS

Additional regulations

OECD. Program to investigate the potential hazards of high production volume further work.

US. TSCA IUR Chemicals Exempt from Update Reporting



Revision Date: 02/26/2007

Print Date: 2/28/2007 MSDS Number: R0371467

Version: 1.2

KNIT/CSM CDM1808GB 50" KNYTEX 23332

US, OSHA Hazard Communication Standard: On One of the Floor Lists of the OSHA HCS (29 CFR 1910.1200).

SARA Hazard Classification Acute Health Hazard

SARA 313 Component(s)

OSHA Hazards

	Health	Flammability	Reactivity	Other
HMIS	1	0	0	
NFPA	1	0	0	

Moderate skin irritant

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances.

This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).