

**PRODUCT NAME: Rhino® 3143 Hardener-TAP Marine 143 Slow Hardener**  
**CHEMICAL FAMILY: Cycloaliphatic Amines****SECTION 1 – IDENTIFICATION****MANUFACTURER'S NAME: Rhino Linings Corporation****ADDRESS: 9747 Businesspark Avenue, San Diego, CA, 92131****INFORMATION PHONE: 858-450-0441****EMERGENCY CONTACT: (CHEMTREC): 800-424-9300****SECTION 2 – HAZARDS IDENTIFICATION**

EMERGENCY OVERVIEW: Epoxy hardener solution. Certain individuals may have pre-existing skin or respiratory conditions causing a sensitivity or allergy which manifests as various reactions. Heating or spraying this product or the mixed parts increases potential health hazards. Health and Safety personnel should examine handling procedures remedy existing and potential health and safety hazards.

**POTENTIAL HEALTH EFFECTS:****EYE:**

- May cause irritation.

**SKIN:**

- May cause irritation.

**INGESTION:**

- May inflame or damage the G.I. tract. Ingestion may be harmful.

**INHALATION:**

- May cause irritation.

**CHRONIC EFFECTS:**

- Repeated exposure may cause irritation and sensitization.

**SIGNS & SYMPTOMS:**

- Skin rash, irritation, reddening, or eczema; Breathing irritation or difficulty.

**SECTION 3 – COMPOSITION/INFORMATION ON INGREDIENTS**

<b>INGREDIENT</b>	<b>%</b>	<b>CAS #</b>	<b>EXPOSURE LIMITS</b>
TETA ,Phenol reaction products	>30	32610-77-8	N/E
Benzyl alcohol	>20	100-51-6	N/E
Phenol	<10	108-95-2	N/E
Proprietary ingredients	<40	Trade secret	N/E

**SECTION 4 – FIRST-AID MEASURES****◆USE APPROPRIATE BLOOD-BORNE PATHOGENS PROTECTIONS◆****EYE:**

- Hold eyelids apart and flood with copious amounts of water. Seek medical attention.

**SKIN:**

- Remove excess product. Wash thoroughly with soap and water. If irritation persists, seek medical attention.

**INGESTION:**

- Do not induce vomiting unless directed by medical personnel. Seek medical attention.

**INHALATION:**

- Remove to fresh air. Seek medical attention.

**SECTION 5 – FIRE-FIGHTING MEASURES**

**PRODUCT NAME: Rhino® 3143 Hardener****CHEMICAL FAMILY: Cycloaliphatic Amines**

FLASH POINT: &gt;210°F UEL: N.D.A.% LEL: N.D.A. VAPOR DENSITY: N.D.A.

NFPA FLAMMABILITY RATING: 1 AUTOIGNITION: N.D.A.

COMBUSTION PRODUCTS: CO, CO<sub>2</sub>, NO<sub>x</sub>, & misc. hydrocarbons

SPECIAL HAZARDS: Firefighters should wear butyl rubber boots, gloves, and body suit with SCBA. May generate toxic and irritating combustion products. Use DOT Response Guide #153.

EXTINGUISHING MEDIA: Use foam, CO<sub>2</sub> dry chemical, water fog.

FIRE FIGHTER INSTRUCTIONS: Stay upwind. Wear at least full bunker gear and SCBA.

**SECTION 6 – ACCIDENTAL RELEASE MEASURES**

Isolate spill area. Keep out of sewer and storm drains. Stop the leak and contain the spill. Vacuum, scoop, or absorb spill with non-combustible materials. Clean up spill residues with soap and water.

**SECTION 7 – HANDLING AND STORAGE**

Avoid skin and eye contact and breathing vapors by appropriate measures. Do not eat or smoke while handling this product. Wash thoroughly with soap and water after handling or exposure to this product.

Store in original sealed container at ambient temperatures (65°-80°F) in dry, well-ventilated areas.

**SECTION 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION**

For Personal exposure Limits (PEL), Threshold Limit Values (TLV), or other exposure limits, see Sec.3.

GENERAL: Provide adequate ventilation that will keep airborne concentration at a minimum.

EYE/FACE: Safety glasses or splash goggles with face shield.

SKIN: Chemical resistant gloves. Don chemical resistant clothing where exposure may occur.

RESPIRATORY: NIOSH approved respirator with organic vapor/HEPA filter cartridges.

OTHER: Decontaminate or discard clothing and materials that have come in contact with this product.

**SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES**

APPEARANCE: amber liquid

ODOR: faint amine

PHYSICAL STATE: liquid

pH: alkaline VAPOR PRESS: N.D.A.

VAPOR DENSITY: N.D.A.

SPECIFIC GRAVITY: 1.05

BOILING PT: N.D.A.

MELT PT: N/A

SOLUBILITY IN H<sub>2</sub>O: slightly**SECTION 10 – STABILITY AND REACTIVITY**

CHEMICAL STABILITY: Stable.

INCOMPATIBILITY: Strong oxidizers, acids, epoxy resins in uncontrolled conditions; contact with other unpolymerized monomers or polymers.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION: None known, other than Sec. 5's Combustion Products.

**SECTION 11 – TOXICOLOGICAL INFORMATION**

Oral: N.D.A.

Dermal: N.D.A.

Inhalation: N.D.A.

Carcinogens under OSHA, ACGIH, NTP, IARC, or Other: None ≥ 0.1%.

**SECTION 12 – ECOLOGICAL INFORMATION**

N.D.A.

**PRODUCT NAME: Rhino® 3143 Hardener**  
**CHEMICAL FAMILY: Cycloaliphatic Amines****SECTION 13 – DISPOSAL CONSIDERATIONS**

Dispose of in accordance with applicable federal, state, and local laws and regulations.

**SECTION 14 – TRANSPORT INFORMATION**DOT: Not Regulated.  
IATA:  
IMO:**SECTION 15 – REGULATORY INFORMATION**OSHA: 1910.1200 Hazardous Chemical "Irritant", "Sensitizer".  
TSCA: Contains listed ingredients.  
SARA III: Sec311 & 312 Immediate Health Hazard; Sec313 Chemicals above de minimus level: None.  
CA PROP. 65 NOTICE: Not listed.  
VOLATILE ORGANIC COMPOUND (VOC) %: Zero.  
NFPA: HEALTH 2 FIRE 1 REACTIVITY 0 OTHER N/AWHMIS: Hazard Classification: Class D2B Skin Sensitizer. Refer to SDS for specific warnings.  
WHMIS Symbols: Stylized T.  
Trade Secrets: N/A.

Hazardous Products Act Information: This product SDS contains ingredients which are Controlled and/or on the Ingredient Disclosure List (HPA sections 13 and 14).

**SECTION 16 – OTHER INFORMATION**

03/25/2015 Change to SDS format. Supercedes 01/04/2012.

ABBREVIATIONS: N/A = not applicable; N.D.A. = no data available; NE = not established

**Disclaimer: The data set forth in this sheet are based on information provided by the suppliers of the raw materials and chemicals used in the manufacture of the aforementioned product. Rhino Linings Corporation makes no warranty with respect to the accuracy of the information provided by their suppliers, and disclaims all liability of reliance thereof.**