Safety Data Sheet E302 Rocket Release®



Copying and/or downloading of this information for the purpose of properly utilizing Stoner Inc. product is allowed provided that: (1) the information is copied in full with no changes unless prior agreement is obtained from Stoner Inc., & (2) neither the copy nor the original is resold or otherwise distributed with intention of earning profit thereon.

1. IDENTIFICATION

Stoner Incorporated 1070 Robert Fulton Hwy. Quarryville, PA 17566 1-800-227-5538	Product Name: Product Code: Product Use: 24-hour emergency phone:	Rocket Release® E302 Mold Release 1-800-424-9300 [CHEMTREC]		
2. HAZARD IDENTIFICA POTENTIAL HEALTH EFFECTS Classification of the chemical in according the second state of the second state	TION ordance with paragraph (d) of §1910.1200;			
GHS Classification	Gases under pressure - Liquified Gas Aspiration Hazard Category 1 Flammable Aerosol Category 2 Skin Corrosion/Irritation Category 2 Specific Target Organ Systemic Toxicity (STOT) - 5	Single Exposure Category 3		
Signal Word	Danger			
Hazard Statements	Flammable aerosol. Contains gas under pressure; may explode if heated. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness.			
Precautionary Statements				
Prevention	Keep away from heat/sparks/open flames/hot surfac Do not spray on an open flame or other ignition sou Pressurized container: Do not pierce or burn, even a Avoid breathing dust/fume/gas/mist/vapours/spray. P264 - Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves/protective clothing/eye protective	irce. ifter use.		
Response	P301+P310 - If swallowed: Immediately call a poiss P302+P352 - If on skin: Wash with plenty of soap IF INHALED: Remove victim to fresh air and keep P312 - Call a poison center, doctor or medical center P321 - Specific treatment (see on this SDS). Do NOT induce vomiting. If skin irritation occurs: Get medical advice/attention	and water. at rest in a position comfortable for breathing. er if you feel unwell.		
Storage	Store in a well-ventilated place. Keep container tigh Store locked up. Protect from sunlight. Store in a well-ventilated plac Protect from sunlight. Do no expose to temperatures	ce.		
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulation for hazardous wastes.			

3. COMPOSITION/INFORMATION ON INGREDIENTS

COMPONENT	CAS #	Percent	
Halogenated hydrocarbon/ether blend	Mixture	80-100	
Aliphatic hydrocarbons	142-82-5	1-20	
Aliphatic hydrocarbon	64741-66-8	1-20	
HMIS® III* HAZARDOUS WARNING	SS:		
Health: 1	Flammability: 2	Physical: 2	Personal See Section 8 Protective

Equipment:

* See www.paint.org/hmis or call the ACA at 1 (202) 462-6272 for more information on this current rating system.

4. FIRST AID MEASURES

Eyes: Immediately flush eyes gently with plenty of water for at least 15 minutes while holding eyelids apart. If symptoms persist or there is visual difficulty, seek medical attention.

Skin Contact: In case of contact, immediately wash contaminated area with plenty of water for at least 15 minutes. For liquid contact, treat for frostbite if necessary. Seek medical attention if symptoms persist. Wash clothing before reuse. Wash the contaminated skin with soap and water.

Ingestion:Do not induce vomiting. Aspiration into the lungs can cause serious damage. If vomiting occurs spontaneously, keep head below
hips to prevent aspiration of liquid into lungs. Contact a physician, medical facility, or poison control center immediately.Inhalation:Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Seek immediate medical
attention.

NOTES TO PHYSICIAN:

Because of possible disturbances of cardiac rhythm, catecholamine drugs, such as epinephrine, should be used only in situations of emergency life support. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. This material is an aspiration hazard. Aspiration during swallowing or vomiting may severely damage the lungs. Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin; lung (for example, asthma-like conditions); kidney; central nervous system; auditory system; arrhythmias (irregular heartbeats);

5. FIRE FIGHTING MEASURES

Fire and/or Explosion Hazards:	This product contains a component(s) that is considered an extremely flammable gas(es), which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. This product contains a component(s) that is considered a flammable liquid, which has vapors that are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, or other flames and ignition sources at locations distant from the material's handling point. Containers may rupture or explode under fire conditions. "Empty" containers retain product residue and can be dangerous.
Fire Fighting Instructions:	Use CO2, foam or dry chemical. Water is generally not effective and may spread fire; however, water spray may be used from a safe distance to cool closed containers and protect surrounding area.

6. ACCIDENTAL RELEASE MEASURES

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:

Ventilate contaminated area. Remove all sources of ignition. Wear appropriate personal protective equipment (PPE). Stop or reduce discharge if it can be done safely. Avoid run-off into storm sewers and ditches which may lead to natural waterways. If runoff occurs, notify authorities as required. Clean up with absorbent material. Place absorbent materials into container and close it tightly. Dispose of container properly.

7. HANDLING AND STORAGE

Handling: Use with adequate ventilation. Do not use near ignition sources. Avoid prolonged or repeated breathing of vapor. Avoid prolonged or repeated contact with skin. May cause frostbite. Normal precautions common to safe manufacturing practice should be followed in handling and storage. This material can be harmful or irritating. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition; they may explode and cause injury or death.
Storage: Storage: Store in a cool, dry, well ventilated area away from all sources of ignition. Do not store at temperatures above 122 degrees F. Store away from oxygen cylinders or other oxidizing materials and possible ignition sources. Ground all equipment and cylinders before use. Empty container may contain residues which are hazardous. Store away from incompatible materials such as materials that support combustion (oxidizing materials) and corrosive materials (strong acids or bases). Normal precautions common to safe manufacturing practice should be followed in handling and storage. Store away from heat and direct sunlight.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering Controls:	Ventilation should be adequate to prevent exposures above the limits indicated below in this section of the SDS (from known, suspected or apparent adverse effects).				
Eye Protection:	Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid or airborne material. Have an eye wash station available.				
Skin Protection:	The use of ch skin.	emically resistant gloves is	recommended if there is a	ny possibility of prolonged of	or repeated liquid contact with
Respiratory Protection:	A supplied air respirator should be used if ventilation is not sufficient to maintain exposure limits. Use NIOSH approved respirator where there is likelihood of inhalation of the product mist, spray or aerosol.				
COMPONENT Halogenated hydrocarbon/ether blendCAS # MixtureACGIH TLV Not establishedOSHA PEL Not establishedOTHER 1000ppm TWA (Mfr.)					
Aliphatic hydrocarbons		142-82-5	400 ppm TWA	Not established	Not established
Aliphatic hydrocarbon		64741-66-8	Not established	500ppm TWA	300ppm TWA-Mfr. Recommended

9. PHYSICAL AND CHEMICAL PROPERTIES

Aerosol can	Lower Flammability Limit (%):	Not applicable
Colorless to pale yellow	Upper Flammability Limit (%):	Not applicable
Slight ethereal.	Vapor Pressure (PSIG @ 70°F):	71.00
Mild	Vapor Density $[air = 1]$:	>1
Not applicable	Relative Density (H2O=1):	0.74
No data available	Solubility in Water:	Not determined
-13.0	Partial Coefficient: n-	No data available
	octanol/water:	
Not applicable	Autoignition Temperature (°F):	474
Not determined	Decomposition Temperature (°F):	No data available
No data available 60 - 80	Viscosity, dynamic (cSt):	No data available
	Colorless to pale yellow Slight ethereal. Mild Not applicable No data available -13.0 Not applicable Not determined No data available	Colorless to pale yellowUpper Flammability Limit (%):Slight ethereal.Vapor Pressure (PSIG @ 70°F):MildVapor Density [air = 1]:Not applicableRelative Density (H2O=1):No data availableSolubility in Water:-13.0Partial Coefficient: n- octanol/water:Not applicableAutoignition Temperature (°F):Not determinedDecomposition Temperature (°F):No data availableViscosity, dynamic (cSt):

10. STABILITY AND REACTION

Chemical Stability:	Stable.
Conditions to Avoid:	Avoid contact with: Ignition sources such as open flames, sparks, static discharges or glowing metal surfaces. Strong
	oxidizing agents.
Decomposition Products:	If heated with peroxides present, violent decomposition can occur. Burning can produce the following combustion
	products: Carbon dioxide and carbon monoxide. Various hydrocarbons.

11. TOXICOLOGICAL INFORMATION

Reproductive & Developmental Toxicity:	No data available.	
IARC Carcinogen Designation:	No data available	
Ingredient Aliphatic hydrocarbons	CAS # 142-82-5	Toxicological Data INHALATION LC50 Rat 103 GM/M3

12. ECOLOGICAL INFORMATION

Ecological Toxicity: Mobility:	May cause long-term adverse effects in the aquatic environment. No data available		
Ingredient Ether propellant	CAS # 115-10-6	Toxicological Data 48HR NOEC GUPPIES > 4000 mg/L 48HR NOEC Daphnia > 4000 mg/L No data available	
Aliphatic hydrocarbons	142-82-5	Aquatic LC50 (24h) Fish = 4 mg/L 48HR EC50 Daphnia = 1.5 mg/L 96HR EC50 Algae = 3.7 mg/L No data available	
Aliphatic hydrocarbon	64741-66-8	No data available 21 DAY NOEC Daphnia 0.17 mg/L No data available	

13. DISPOSAL CONSIDERATIONS

Disposal : Dispose according to Federal, State and local regulations.

14. TRANSPORTATION INFORMATION

Agency	UN Number	Proper Shipping name	Hazard Class	Packing Group
DOT	UN1950	Aerosols, Flammable†	2.1	Not applicable
IATA	ID8000	Consumer Commodity†	9	Not applicable
IMDG	UN1950	Aerosols, Flammable†	2.1	Not applicable

† "Limited Quantities" may be applicable for this transportation mode.

15. REGULATORY INFORMATION

Warning: This product contains the following chemicals that are subject to reporting requirements for the following regulatory bodies listed below:COMPONENTCAS #% BY WEIGHTRegulatory BodyNo components listed in this section.SARA Section 313

Toxic Substances Control Act

All components of this product are listed on the TSCA inventory.

California Prop 65

This product contains no California Proposition 65 ingredients that cause cancer, birth defects or other reproductive harm.

16. OTHER INFORMATION

Other Information : SDS Prepared by L. Dean Swartz, SDS Coordinator

Version Date: 12/12/17

This information contained in this SDS is believed to be accurate as of the version date, but is not warranted to be. Since the use of this information and the conditions of use of this product are not within the control of Stoner Inc, it is the user's obligation to determine the conditions of safe use.