




Stir so that stick scrapes entire wall of container.



Bring up liquid from bottom of cup to blend



Stir center. Repeat steps to thoroughly mix liquids.

WARRANTY

TAP products are manufactured to quality specifications, however they should be tested to determine their suitability for your application. Since we have no control over working conditions or methods, our liability does not exceed the value or replacement of this product. TAP Resin products are guaranteed for six months from date of purchase or nine months from code date on container.

Date Code: 22310

FOUR TO ONE



SUPER HARD EPOXY HARDENER

- Super hard cure
- No VOC's • Low viscosity
- Excellent chemical resistance
- Good adhesive for most porous and nonporous surfaces

See CAUTIONS on Label.

Net 32 fl oz • .946 L

Use with 1 Gallon Super Hard Resin

TAP Plastics Inc.

San Leandro, CA 94577

Quality Products Since 1952

EQUIPMENT NEEDED:

- Bristle brushes
- Squeegee
- Rubber gloves
- Mixing containers
- Stir sticks
- Sandpaper
- Particle masks for sanding
- Acetone for cleaning tools and equipment before resin cures

CAUTIONS

Use in well ventilated area. Use rubber gloves to avoid skin contact. Remove from skin with soap and water. If eye contact occurs, wash immediately with clean water for 15 minutes and contact an eye specialist immediately. If swallowed, do not induce vomiting and consult a physician. KEEP AWAY FROM CHILDREN.

HELPFUL HINTS

- Always make a patch test before large or critical jobs, especially where chemical resistance is required.
- Surface temperature of part is as critical as surrounding air temperature.
- May be used for electrical potting but is not recommended for casting over 1/8" thick.

TAP Product Bulletin 3 and Technical Datasheet are available on our website: tapplastics.com

Rev. 9/19/11