

**SCS2002 12C-Crtrg (0.986 Lbs-0.448 Kg)
 Silicone Rubber Sealant White Sil-Pru**
1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: GES Waterford Plant
 260 Hudson River Rd
 Waterford NY 12188
Revised: 07/20/2005
Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Silicone Rubber
Formula: Mixture

HMIS

Flammability: 1 Reactivity: 0 Health: 1 Prot. Equipm.:

NFPA

Flammability: 1 Reactivity: 0 Health: 1 Special Haz.:

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<u>A. HAZARDOUS</u>		
Methyltrimethoxysilane	1185-55-3	1 - 5 %
<u>B. NON-HAZARDOUS</u>		
Titanium oxide	13463-67-7	1 - 5 %
Treated fumed silica	68583-49-3	1 - 5 %
Polydimethylsiloxane	63148-62-9	10 - 30 %
Dimethylpolysiloxane	70131-67-8	30 - 60 %
Calcium carbonate	1317-65-3	30 - 60 %

3. HAZARDS IDENTIFICATION
EMERGENCY OVERVIEW

WARNING! Irritating to eyes, respiratory system and skin. May be harmful if swallowed.

Form: solid Color: white Odor: none

POTENTIAL HEALTH EFFECTS
INGESTION

May be harmful if swallowed.

**SCS2002 12C-Crtrg (0.986 Lbs-0.448 Kg)
Silicone Rubber Sealant**

SKIN

Uncured product contact will irritate lips, gums and tongue. Skin irritation is possible after contact with the uncured product.

INHALATION

May cause mild respiratory irritation. Applies in uncured state.

EYES

Eye irritation on contact with the uncured product.

MEDICAL CONDITIONS AGGRAVATED

None known.

SUBCHRONIC (TARGET ORGAN)

None known.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

dermal; Eyes

OTHER

Methanol released during curing. This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 F (150 C) and above in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. An MSDS for formaldehyde is available from GE Advanced Materials - Silicones.

4. FIRST AID MEASURES**INGESTION**

Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

SKIN

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

**SCS2002 12C-Crtrg (0.986 Lbs-0.448 Kg)
Silicone Rubber Sealant**

NOTE TO PHYSICIAN

None known.

5. FIRE-FIGHTING MEASURES

FLASH POINT:

METHOD:

not applicable

IGNITION TEMPERATURE:

Unknown

FLAMMABLE LIMITS IN AIR - LOWER (%):

not applicable

FLAMMABLE LIMITS IN AIR - UPPER (%):

not applicable

SENSITIVITY TO MECHANICAL IMPACT:

No

SENSITIVITY TO STATIC DISCHARGE

Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA

All standard extinguishing agents are suitable.none

SPECIAL FIRE FIGHTING PROCEDURES

Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED

Wipe, scrape or soak up in an inert material and put in a container for disposal. Wash walking surfaces with detergent and water to reduce slipping hazard. Wear proper protective equipment as specified in the protective equipment section. Increase area ventilation.

7. HANDLING AND STORAGE

STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE

Avoid contact with skin and eyes. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation. Use only in well-ventilated areas. Keep away from children. Store away from heat, sources of ignition, and incompatibles. Product releases methanol during application and curing.

**SCS2002 12C-Crtrg (0.986 Lbs-0.448 Kg)
 Silicone Rubber Sealant**
8. EXPOSURE CONTROLS / PERSONAL PROTECTION
ENGINEERING CONTROLS

Eyewash stations; Showers

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29 CFR 1910.134).

PROTECTIVE GLOVES

Cloth gloves.

EYE AND FACE PROTECTION

safety glasses

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	not applicable
VAPOR PRESSURE (20 C) (MM HG):	negligible
VAPOR DENSITY (AIR=1):	negligible
FREEZING POINT:	not applicable
MELTING POINT:	not applicable
PHYSICAL STATE:	solid
ODOR:	none
COLOR:	white
EVAPORATION RATE (BUTYL ACETATE=1):	< 1
SPECIFIC GRAVITY (WATER=1):	ca. 1.40
DENSITY (KG/M3):	ca. 1,400.00 KG/M3
ACID / ALKALINITY (MEQ/G):	Unknown
pH:	not applicable
VOLATILE ORGANIC CONTENT (VOL):	2.00 %(m)
SOLUBILITY IN WATER (20 C):	negligible
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	Toluene

**SCS2002 12C-Crtrg (0.986 Lbs-0.448 Kg)
Silicone Rubber Sealant**

VOC EXCL. H2O & EXEMPTS (G/L): 20.00

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION

Will not occur

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon monoxide; carbon dioxide (CO₂); Silicon dioxide.; Methanol; formaldehyde

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

None known.

ACUTE DERMAL

None known.

ACUTE INHALATION

None known.

OTHER

no data available

SENSITIZATION

not applicable

SKIN IRRITATION

not applicable

EYE IRRITATION

not applicable

MUTAGENICITY

Unknown

**SCS2002 12C-Crtrg (0.986 Lbs-0.448 Kg)
Silicone Rubber Sealant**

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGY

Ecotoxicological data for this product is not available.

CHEMICAL FATE

no data available

DISTRIBUTION

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Not Regulated if Section is Blank

15. REGULATORY INFORMATION

Inventories

Canada DSL Inventory	y (positive listing)
Korea Existing Chemicals Inventory (KECI)	y (positive listing)
China Inventory of Existing Chemical Substances	y (positive listing)
Australia Inventory of Chemical Substances (AICS)	y (positive listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (positive listing)
EU list of existing chemical substances	y (positive listing)
Canada NDSL Inventory	n (Negative listing)
Japan Inventory of Existing & New Chemical Substances (ENCS)	q (quantity restricted)
TSCA list	y (positive listing)

For inventories that are marked as quantity restricted or special cases, please contact GE.



**SCS2002 12C-Crtrg (0.986 Lbs-0.448 Kg)
Silicone Rubber Sealant**

US Regulatory Information

CERCLA

PRODUCT COMPOSITION

Chemical

CERCLA Reportable Quantity

CLEAN AIR ACT

CLEAN WATER ACT

SARA SECTION 302

SARA (311,312) HAZARD CLASS

Acute Health Hazard

SARA (313) CHEMICALS

Canadian Regulatory Information

WHMIS HAZARD CLASS

D2A VERY TOXIC MATERIALS, D2B TOXIC MATERIALS

Other

SCHDLE B/HTSUS:

3214.10.00.10 Mastic based on rubber

ECCN:

EAR99

CALIFORNIA PROPOSITION 65

This product does not contain any chemicals known to State of California to cause cancer, birth defects or any other harm.

16. OTHER INFORMATION

OTHER

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found
NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm =



**SCS2002 12C-Crtrg (0.986 Lbs-0.448 Kg)
Silicone Rubber Sealant**

parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status
not required under 40 CFR part 720.30(h-2).