



the fantastic plastic place

Product Data

Mylar Film Pressure Sensitive

Clear polyester film .002 thick coated with a permanent pressure sensitive adhesive.

APPLICATION

This product is intended for use in applications requiring clarity, durability, high temperature and dimensional stability.

MINIMUM APPLICATION TEMPERATURE

+ 35° F. For lower application temperature requirements.

SERVICE APPLICATION TEMPERATURE

- 50° F to + 275° F.

TRANSPARENCY

Clear film and/or adhesive will exhibit no yellowing or loss transparency after two years of normal vertical exposure.

EXPECTED LIFETIME EXTERIOR

Polyester films are not recommended for outdoor use.

WATER RESISTANCE

Excellent.

HUMIDITY RESISTANCE

Excellent.

SOLVENT RESISTANCE

Good for most petroleum solvents and lower aliphatic alcohols.
For ultimate solvent resistance, edge sealing is recommended.

SHELF LIFE

Two (2) year when stored under conditions of 70°F and 50% relative humidity.

December 2016

Visit our website: tapplastics.com

TAP Plastics Corporate Office • 3011 Alvarado Street, Suite A • San Leandro, CA 94577 • 510.895.8249 • Fax 510.895.9613
15 TAP stores in Northern California • 2 in Oregon • 3 in Washington
For the location nearest you go to tapplastics.com